

LNIS36



Features

Weatherproof IR/Day and night IP Camera

SONY/SHARP Color CCD

M-JPEG4,32Bit RSIC Embedded Proccsser

IR LED: ϕ 5X36PCS ,IR Distance: 30M

Water Resistance : IP66

Lens: Board Lens 6mm/F2.0(Optional)

Dimension : 208(W)x83(H)x83(D)mm



Specifications

Model	LNIS36S
Image Sensor	1/3"SONY
Horizontal Resolution	420 TV Line
Pixels	704(H) \times 576(V)
Operate system	Windows 2000/XP, Linux
IR LED	ϕ 5 X 36 PCS
IR Series Distance	30 M
Lens	Board Lens 6mm/F2.0 (Optional)
Sync System	Internal
IR Status	Under 10 Lux By CDS
Usable Illumination	0 Lux/F2.0 (LED ON)
IR Power On	CDS Auto Control
S/N Ratio	\geq 48dB (AGC OFF)
Gamma Correction	0.45
Video Out	Composite Signal (1.0Vp-p, 75 Ω)
Operation Temperature	-10 $^{\circ}$ C ~ +50 $^{\circ}$ C RH95% Max
Storage Temperature	-20 $^{\circ}$ C ~ +60 $^{\circ}$ C RH95% Max
White Balance	Auto
Power Source	DC12V 350mA
Dimension	208(W)x83(H)x83(D)mm
Weight	1200g