

LNIS60**Features**

Weatherproof IR Network Camera

SONY/SHARP Color CCD

M-JPEG4,32Bit RSIC Embedded Proccsser

IR LED: ϕ 5X60PCS ,IR Distance: 50M

Water Resistance : IP66

Lens: Board Lens 8mm/F2.0(Optional)

Dimension :143(W)x78(H)x56(D)mm

**Specifications**

Model	LNIS60S	LNIS60H
Image Sensor	1/3"SONY	1/3"SHARP
Horizontal Resolution	420 TV Line	
Pixels	704(H)×576(V)	
Operate system	Windows 2000/XP, Linux	
IR LED	ϕ 5 X 60 PCS	
IR Series Distance	50 M	
Lens	Board Lens 8mm/F2.0(Optional)	
Sync System	Internal	
IR Status	Under 10 Lux By CDS	
Usable Illumination	0 Lux/F2.0 (LED ON)	
IR Power On	CDS Auto Control	
S/N Ratio	≥48dB (AGC OFF)	
Gamma Correction	0.45	
Video Out	Composite Signal (1.0Vp-p, 75Ω)	
Operation Temperature	-10℃ ~ +50℃ RH95% Max	
Storage Temperature	-20℃ ~ +60℃ RH95% Max	
White Balance	Auto	
Power Source	DC5V 2000mA	
Dimension	143(W) x 78(H) x 56(D)mm	
Weight	1500g	