

H.264 Stand-alone DVR

LS-8004H



Features

- ⋄ H.264 Baseline: 9 selectable video quality levels
- ⋄ Hexaplex operation - simultaneous record, live, playback, backup, control, & remote access
- ⋄ Mixed operation windows - Playback Search for selected channel in the live monitoring mode
- ⋄ Recording quality can be configured into two groups - better usage of hard disk
- ⋄ 5 network clients supported
- ⋄ Network audio conferencing capability
- ⋄ Playback search by time or event (alarm, motion, & video loss)
- ⋄ Multilingual support
- ⋄ Multi-level password to ensure high degree of security

Specifications

Model Number	LS-8004H
Video Input Format	NTSC / PAL : BNC 4CH In / 1CH Out / SPOT Out
Display Resolution	NTSC : 720x480 ; PAL: 720x576
Recording Frame rate (IPS) & Resolution	NTSC : 30/720x480; 60/720x240; 120/360x240 PAL : 25/720x576; 50/720x288; 100/360x288
Compression Method	Video: H.264 Baseline Audio: ADPCM
Hard Disk Capacity	Over 500G Bytes , ATA-100 interface HDD x 1
Recording Time	7~20 days with 500GB HD for Continuous Recording mode @ 25 fps
Recording Mode	Continuous, Motion detection, Sensor activated, Time schedule
Sensors, Alarm	4 Input, 1 Output (Alarm)
Audio	2CH in, 2CH out
Network	1 RJ-45 10/100Mbps Ethernet connector
Media Backup	1 SD slot (Option)/1 USB 2.0 ports for USB 2.0 flash disks, DVD+RW, DVD±R, card readers, HDD
VGA Output	1CH
PTZ Control	RS-485/RS-232
IR Remote Controller	Yes
Operating Temperature	0°C~+50°C
Power Input	DC 12V/ 5A
Dimensions(L×W×H)	315mm×250mm×52mm