

## LS-8004T



### Features

Small & exquisite design for homes, small retail stores, or business premises

The Third Generation MJPEG compression

Available in NTSC & PAL system

Display resolution: 720×480(NTSC)/720×576(PAL)

Real-time display: 120fps(NTSC)/100fps(PAL)

Selectable 24hrs. continuous, motion detection recording mode

Selectable motion detection area & sensitivity adjustment for individual camera

PC playback & backup via built-in USB 2.0 port (D3593 only)

With auto switch display function

With power recovery auto-record function

Fixed/removable HDD caddy supports up to 200GB IDE HDD×1

IR remote control included(optional)



### Specifications

|                      |   |          |                           |              |
|----------------------|---|----------|---------------------------|--------------|
| <b>Model</b>         | <b>LS-8004T</b>   |          |                           |              |
| Compression Format   | Motion JPEG(12~20K Bytes per frame)   |          |                           |              |
| Video Input / Output | BNC 4-channel inputs / 1-channel outputs (Composite)                            |          |                           |              |
| Display Mode         | Quad; full screen of single picture; auto switch                                |          |                           |              |
| Display Frame Rate   | NTSC: 120fps / 4x30fps PAL: 100 fps / 4x25fps                                   |          |                           |              |
| Recording Frame Rate | NTSC: max. 30fps / 4x7.5 PAL: max. 25fps / 4x6.25fps                            |          |                           |              |
| Display Resolution   | NTSC: 720x480 PAL: 720x576  |          |                           |              |
| Recording Resolution | NTSC: 320x112, 640x224 PAL: 320x136, 640x272                                    |          |                           |              |
| HDD Rack             | Removable HDD caddy supports up to 200GB IDE HDD                                |          | Fixed HDD rack            |              |
| Recording Time       | NTSC: 155 hours with 120GB HDD @ 15fps<br>PAL: 194 hours with 120GB HDD @ 12fps |          |                           |              |
| Recording            | Selectable 24 hrs. continuous; motion detection; auto record                    |          |                           |              |
| USB                  | N/A   | USB2.0   | N/A                       | N/A USB2.0   |
| Remote               | N/A   | Included | Optional                  | N/A Included |
| Power                | DC 12V, 3A  |          |                           |              |
| Dimensions (D*W*H)   | 258X132X80mm  |          | 200X132X80mm 258X132X80mm |              |