

MPEG2/4 Stand-alone DVR

LS-8009MR



Features

- ⋮ MPEG2/4 video compression - user selectable recording picture quality
- ⋮ Selectable recording mode: 24hrs continuous, motion detection, sensor triggered
- ⋮ Selectable motion detection area & sensitivity adjustment for individual camera
- ⋮ Password protection
- ⋮ Easy back up via USB or CD-RW, DVD-R (Option)
- ⋮ Network function: remote control DVR (monitoring, playback) IE based
- ⋮ Hidden channel recording function

Specifications

Model Number	LS-8009MR
Compression Format	MPEG2 Recording , MPEG4 Network Streaming
Video Input/Output	BNC 9-channel input/1-channel output
Audio Input/Output	RCA 2-channel input/1-channel output
Display Frame Rate	NTSC: 270/9X30 fps PAL: 225/9X25 fps
Display Resolution	NTSC: 720x480 PAL: 720x576
Recording Frame Rate	(configurable) NTSC: max.60fps PAL: max.50fps
Recording Quality	9 Recording Quality Levels
HDD Rack	Default: One removable rack + one fixed HDD inside, ATA or SATA Option: One CD-RW + one fixed HDD rack inside
Recording Mode	24hrs. Continuous, motion detection, sensor triggered, network
USB Port	USB2.0
Network Interface	RJ45
P/T/Z	RS485
Remote Controller	Included
Power Adapter	DC12V, 5A
Storage Temp.&Humidity	-20~65oC/20~95%RH(Without condenser)
Working Temp.&Humidity	-5~50oC/20~80%RH(Without condenser)
Dimension(LxWxH)	345X370X70mm