

LISB



Features

Weatherproof IR Camera

SONY/SHARP Color CCD

Water Resistance : IP66

Auto White Balance(AWB)

Lens: 4-9mm Manual Zoom Lens

Dimension : 65(W) x 108(H) x 55(D)mm



Specifications

Model	LISBSH	LISBSH	LISBS	LISBSF	LISBHF
Image Sensor	1/3"SONY		1/3"SONY	1/4"SONY	1/4"SHARP
Horizontal Resolution	540 TV Line	480 TV Line	420 TV Line		
Pixels	PAL:795 (H)× 596 (V) NTSC :811 (H)× 508 (V)	PAL:752(H)×582 (V) NTSC:768(H)× 494(V)	PAL:500(H)× 582(V) NTSC:510(H)× 492(V)		
TV System	PAL/NTSC				
Lens	4-9mm Manual Zoom Len				
Sync System	Internal				
Usable Illumination	0.8Lux		0.8Lux		1.0Lux
S/N Ratio	≥ 48dB (AGC OFF)				
Gamma Correction	0.45				
Video Out	Composite Signal (1.0Vp-p, 75Ω)				
Scanning System	PAL:625 Lines, 50 Field/Sec;NTSC:525 Lines, 60 Field/Sec				
Electronic Shutter Time	Auto:PAL 1/50-1/100,000Sec;NTSC 1/60-1/100,000Sec				
Operation Temperature	-10℃ ~ +50℃ RH95% Max				
Storage Temperature	-20℃ ~ +60℃ RH95% Max				
White Balance	Auto				
Power Source	DC12V 250mA				
Dimension	65(W) x 108(H) x 55(D)mm				
Weight	650g				