



SPECIFICATION

Model	PT5A022S500
Camera	
Image Sensor	1/2.5" Aptina 5.1MP High Performance CMOS Sensor
Horizontal Resolution	5MP
Compression	H.264/H265
S/N Ratio	>50db
PTZ	
Horizontal Rotation Speed	45°/S
Horizontal Rotation Range	0°~360°
Tilt Rotation Speed	30°/s
Tilt Rotation Range	0°~93°
Preset Points	220
Guard Tours	3 groups
Guard Points	Max.16 points
Lens	
Focus Length	3.9mm-85.5mm
Focus Control	22X Optical Zoom
Night Vision	
Infrared LED	∅ 42x6PCS
IR Range	60m
Day-night mode	AUTO
Network	
Network protocol	TCP/IP, HTTP, FTP, RTSP, UPnP, DNS, NTP, RTP, UDP, IGMP,P2P
ONVIF	Support
Network interface	Built-in RJ45 network interface,support 10M/100M IP DATA
Stream type	Main Stream / Sub Stream / MJPEG
Interface	
Audio	Optional
Alarm	/
POE	Optional
General	
Weatherproof	IP66
Operating Temperature	Indoor: 0°~ +40° Outdoor: -40°~ +60°
Operating Humidity	≤90% Non Condensing
Power	DC12V 2A/3A
Lightning Protection	Transient voltage 6000V
Dimension	29.5x28x17(cm)
Weight	4.2Kgs