



## SPECIFICATION

<b>Model</b>	<b>PTDA4XGC200</b>
<b>Camera</b>	
Image Sensor	1/2.9" Progressive Scan CMOS Sensor
Horizontal Resolution	2MP
Compression	H.264/H.265
S/N Ratio	60db
<b>PTZ</b>	
Horizontal Rotation Speed	25°/S
Horizontal Rotation Range	0°~350°
Tilt Rotation Speed	20°/S
Tilt Rotation Range	0°~70°
Preset Points	255
Guard Tours	8 groups
Guard Points	Max.20 points
<b>Lens</b>	
Focus Length	3.35-10.05mm F1.7-F3.0
Focus Control	4X Optical Zoom
<b>Night Vision</b>	
Infrared LED	Φ 28x4PCS
IR Range	20m
Day-night mode	AUTO
<b>Network</b>	
Network protocol	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP,SMTP
ONVIF	Support (PROFILE S,PROFILE G,PROFILE T)
Network interface	Built-in RJ45 network interface,support 10M/100M IP DATA
Main Stream1	1920*1080@30fps
Main Stream2	1280*720@30fps
Main Stream3	/
Main Stream4	/
Main Stream5	/
Main Stream6	/
Sub Stream1	720*480@30fps
Sub Stream2	352*288@30fps
Sub Stream3	/
Sub Stream4	/
<b>Interface</b>	
Audio	Optional
Alarm	/
SD Card Slot	/
POE	Optional
<b>General</b>	
Weatherproof	IP66
Operating Temperature	Indoor: 0°~ +40° Outdoor: -15°~ +60°
Operating Humidity	≤90% Non Condensing
Power	DC12V/2A
Lightning Protection	Transient voltage 3000V
Dimension	14x14x13(cm)
Weight	0.55Kgs