



SPECIFICATION

Model NO.	NVR2108DP3FE500	
Package		
NVR	1x NVR2108DP	
Camera	4 x LIRDBAFE500 4 x LBH30FE500	
Cable	8x 20m CAT5e Cable	
Mouse	1xUSB 2.0 Mouse	
Hard Disk	No	
Adaptor	DC52V/2.5A	
Weight	12.8kg/SET	
Camera Model	LIRDBAFE500	LBH30FE500
Image Sensor	1/2.9" Full HD CMOS Sensor	
Resolution	4MP	
Effective Pixels	2608(H)*1952(V)	
Compression	H.264/H.264+/H.265/H.265+/JPEG/AVI	
TV System	PAL/NTSC	
Electronic Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/30-1/10000Sec	
Minimum Illumination	0.01Lux	
S/N Ratio	≥52dB	
Scanning System	Progressive	
Video Output	Network	
Reset Button	Optional	
Lens		
Focus Length	3.6mm	
Focus Control	Fixed	
Lens Type	Fixed	
Pixels	5MP	
Night Vision		
Infrared LED	14μ x 18PCS	14μ x 20PCS
Infrared Distance	20M	25M
IR Status	Auto Control	
IR Power On	Auto Control	
Network		
Ethernet	RJ-45 (10/100Base-T)	
Wireless	/	
Protocol	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP,SMTP,UDP	
ONVIF	Support ONVIF 2.4(Profile S/T/G)	
P2P	YES	
POE	Yes, Support IEEE 802.3af	
Video Delay	0.3S (Within the Lan)	
Main Stream 1	2592*1944@20fp 2560*1920@20fp	
Main Stream 2	2560*1440@30fp	
Main Stream 3	1920*1080@30fps 1280*720@30fps	
Sub Stream 1	720*480@20fps 720*480@30fps	
Sub Stream 2	/	
Sub Stream 3	/	
Tri Stream	/	
IE Brower	IE8-11, Google Chrome, Firefox , Mac Safari	
Smart Phone	iPhone, iPad, Android, Android Pad	
Camera Features		
Day/Night	Color/ B&W (IR-CUT)	
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, White Balance, FLK(Flicker Control)	
Starlight	/	
Corridor Pattern	Support	
Defog Mode	Support	
ROI	/	
BLC	YES	
HDR	/	
WDR	NO	
Motion Detection	Support	
Privacy Masking	3 Rectangular Zone	

Recording Mode	NVR	
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Arabic, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian, Nederlands, Czech, Vietnamese	
Interface		
Audio	Optional	
Alarm	/	
SD Card Slot	/	
RS485	/	
General		
Housing	Metal , IP67	
Anti-cut Bracket	NO	YES
IR Cut Filter	YES	
Operation Temperature	-20℃ ~ +60℃ RH95% Max	
Storage Temperature	-20℃ ~ +60℃ RH95% Max	
Power Source	DC12V±10%, 750mA	DC12V±10%, 950mA
Dimension	φ93 x 74(H) mm	157(W) x 70(H) x 66(D)mm
Weight	400g	650g
Model	NVR2108DP	
System		
Main Processor	ARM Cortex A7 Processor	
Operating System	Embedded LINUX	
Video		
Input	16CH (3840×2160, 2592×1944, 2048×1536, 1920×1080, 1280×960, 1280×720, etc)	
Output	1 VGA, 1 HD	
Audio		
Input	1 Port RCA	
Output	1 Port RCA(Linear, 1kΩ)	
Audio Bit Rate	64kbps	
Audio Compression standard	G711u, G711a, ADPCM_DVI4	
Alarm		
Sensor Input	4	
Output	1	
Motion Detection	16 Channel, MD Zones: 396 (22 × 18)	
Trigger Events	Recording, Email, FTP, Snapshot, Buzzer and Screen Tips, alarm output	
Display		
HD Output	Resolution:4K (3840 × 2160)/30Hz, 4K (3840 × 2160)/30Hz, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz	
VGA	Resolution:1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz	
Display Split	16CHxD1/9CHxD1/8CHxD1/4CHxD1/1CHx1080P/1CHx3MP/1CHx4MP/1CHx5MP/1CHx4k	
Digital Zoom	YES	
OSD	Camera Title, Time, Recording, Motion Detection, Event Alarm	
Recording		
Video Compression	H265/H264/H265+/H264+	
Resolution	4k(3840×2160),5MP(2592×1944),4MP(2688×1520/2560×1440),3MP(2048×1536),1080P(1920×1080),960P(1280×960),720P(1280×720),D1 (720×576/720×480)	
Record Rate	PAL :4k@10×25fp,5MP@14×25fp,4MP@16×25fp,3MP@16×25fp,1080P@16×25fp, 960P@16×25fp,720P@16×25fp, D1@16×25fp NTSC: 4k@10×30fp,5MP@14×30fp,4MP@16×30fp,3MP@16×30fp,1080P@16×30fp, 960P@16×30fp, 720P@16×30fp, D1@16×30fp	
Record Mode	Manual\Timer\Motion Detection\ Alarm\Motion and Alarm\Smart Alarm	
Playback & Backup		
Local Sync Playback	1CH 4K@30fps, 1CH 5MP@30fps,2CH 4MP@30fps, 2CH 3M@30fps, 4CH 1080P@30fps, 4CH 960P@30fps, 4CH 720P@30fps	
Decode Capability	4CH 1080P(1920x1080)@30fps	
Remote Sync Playback	YES	
Search Mode	ALL, Channel, Manual, Time, Date, Motion Detection,Event Alarm,Tag search	
Playback Functions	Play, Pause, Stop, Rewind, Fast play, Slow Play, Full Screen, Frame Play ,Frame Rewind, Digital Zoom,tag,clip	
Backup Mode	USB Device/Network	
Network		
Interface	9 x RJ45 (10M/100M Adaptive Ethernet Interface)	
Incoming Bandwidth	80MB	
Network Functions	TCP/IP, HTTP, UPnP, DNS, NTP, SMTP, DHCP, FTP, DDNS, RTSP, RTCP, p2p,PPPOE	
Onvif	Support onvif S,onvif T	
Web Browser	IE8-11, Google Chrome, Firefox , Mac Safari	
CMS Software	Support Windows 7/ Windows 8/Windows 10/MAC OS	
Cloud Support(P2P)	Yes	
Smart Phone	iPhone, iPad, Android, Android Pad	
POE	8 x Independent 100Mbps POE Network Interfaces(Output PowerAT mode 30W, AF mode 15W per Interface), 45/78 line order, Total Power Output ≧ 100W, Support Plug and Play, Support network cable extended mode Max. 200M	
WIFI	/	
Storage		
Interface Type	1 SATA Hard Disk Interface (2.5"/3.5" SATA)	
Capacity	Up to 8TB capacity	
eSATA	/	
General		
Language	Traditional Chinese, Simplified Chinese, English, Polish, Czech, Russian, Thai, Hebrew, Arabic, Bulgarian, German, French, Portuguese, Turcic, Spanish, Italian, Hungarian, Romanian, Korean, Dutch, Greek, Vietnamese,Janpanese	
USB Interface	2 USB 2.0 Interfaces	
RS485	/	
Power Supply	DC 52V/2500mA ≤10W (Without Hard Disk and POE)	
Working Environment	-10~55℃/10~90%	
Dimension(W×D×H)	260*215*43(mm)	
Weight	2.0KG (without HDD)	