



SPECIFICATION

Model NO.	BMSCHTC500FKE	BMSCTHC500FKE
Video Output Mode	AHD: 8M@15fps, 5M@20fps/12.5fps, 4M/2M@30fps/25fps; TVI/CVI: 8M@15fps/12.5fps,5M@20fps/12.5fps,4M/2M@30fps/25fps	
Camera		
Image Sensor	1/2.5" CMOS sensor	
Image Resolution	8M:3840*2160 5M:2592*1944 4M:2560*1440 2M:1920*1080	
TV System	PAL/NTSC	
Electronic Shutter	Auto	
Minimun Illumination	0.01Lux	
Scanning System	Progressive Scan	
Lens		
Focus Length	3.6mm	
Focus Control	Fixed	
Lens Type	Fixed	
Night Vision		
IR Cut Filter	YES	
Infrared LED	42μ x 2PCS	
Infrared Distance	25M	
IR Status	AGC Auto Control	
Camera Features		
Starlight	/	
Day/Night	YES/NO	
OSD Menu	YES	
WDR	DWDR	
UTC	YES	
Noise Reduction	DNR	
Coaxial Audio	YES (only TVI)	
White Balance	AUTO / MANUAL	
Gain Control	AUTO	
General		
Housing	Metal, IP67	
Bracket	YES	
Operation Temperature	-10℃ ~ +60℃ RH95% Max	
Storage Temperature	-20℃ ~ +60℃ RH95% Max	
Power Source	DC12V±10%, 500mA	
Dimension	70(W) x 67.5(H) x 169(L)mm	
Weight	600g	