

# Longse



## SPECIFICATION

<b>Model NO.</b>	<b>CMSBHTC500FKE</b>	<b>CMSBTHC500FKE</b>
<b>Video Output Mode</b>	AHD: 8M@15fps, 5M@20fps/12.5fps, 4M@30fps/25fps/15fps, 2M@30fps/25fps; TVI: 8M@15fps/12.5fps,5M@20fps/12.5fps,4M@30fps/25fps/15fps, 2M@30fps/25fps; CVI: 8M@15fps/12.5fps,5M@20fps/12.5fps4M/2M@30fps/25fps	
<b>Camera</b>		
Image Sensor	1/2.5" CMOS sensor	
Image Resolution	8M:3840*2160 5M:2592*1944 4M:2560*1440 2M:1920*1080	
TV System	PAL/NTSC	
Electronic Shutter	Auto	
Minimum Illumination	0.01Lux	
Scanning System	Progressive Scan	
<b>Lens</b>		
Focus Length	3.6mm	
Focus Control	Fixed	
Lens Type	Fixed	
<b>Night Vision</b>		
IR Cut Filter	YES	
Infrared LED	42μ x 2PCS	
Infrared Distance	25M	
IR Status	AGC Auto Control	
<b>Camera Features</b>		
Starlight	/	
Day/Night	YES/NO	
OSD Menu	YES	
WDR	DWDR	

UTC	YES
Noise Reduction	DNR
Coaxial Audio	YES (only TVI )
White Balance	AUTO / MANUAL
Gain Control	AUTO
<b>General</b>	
Housing	Metal, IP67
Bracket	NO
Operation Temperature	-10°C ~ +60°C RH95% Max
Storage Temperature	-20°C ~ +60°C RH95% Max
Power Source	DC12V±10%, 500mA
Dimension	∅ 96 x 91(H) mm
Weight	600g