

# Longse



## SPECIFICATION

<b>Model</b>	<b>PT6B018XGL500</b>
<b>Camera</b>	
Image Sensor	1/2.8" Progressive Scan CMOS Sensor
Horizontal Resolution	5MP
Compression	H.264/H.265
Minimum Illumination	Color: 0.008 Lux @ (F1.6, AGC ON), B/W: 0 Lux with IR
S/N Ratio	60db
<b>PTZ</b>	
Horizontal Rotation Speed	120°/sec
Horizontal Rotation Range	0°~360°
Tilt Rotation Speed	60°/sec
Tilt Rotation Range	0°~93°
Preset Points	255
Guard Tours	8 groups
Guard Points	Max 20 points
<b>Lens</b>	
Focus Length	5.35-96.3mm F1.8-F3.9
Focus Control	18X Optical Zoom
<b>Night Vision</b>	
Infrared LED	∅ 35x7PCS IR LEDs + 2PCS Laser LED
IR Range	120m
Day-night mode	AUTO
<b>Network</b>	

Network protocol	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP,SMTP
ONVIF	Support (PROFILE S,PROFILE G,PROFILE T )
Network interface	Built-in RJ45 network interface,support 10M/100M IP DATA
Main Stream1	5MP(2592*1944)@20fps
Main Stream2	4MP(2560*1440)@25fps
Main Stream3	1080P(1920*1080)@30fps
Main Stream4	720P(1280*720)@30fps
Main Stream5	N/A
Main Stream6	N/A
Sub Stream1	D1(720*480)@20fps
Sub Stream2	CIF(352*288)@20fps
Sub Stream3	N/A
Sub Stream4	N/A
<b>AI Function</b>	
Intelligent Analysis	Intrusion Detetion,motion detection based on human detection
<b>Interface</b>	
Audio	Optional
Audio Encode	G711A, C711U
Alarm	N/A
SD Card Slot	Optional
POE	N/A
<b>General</b>	
Weatherproof	IP66
Operating Temperature	Indoor: 0°~ +40° Outdoor: -40°~ +60°
Operating Humidity	≤90% Non Condensing
Power	DC12V/3A
Lightning Protection	Transient voltage 6000V
Dimension	25x21.5x41(cm)
Weight	6.7Kgs