



## SPECIFICATION

<b>Model</b>	<b>HT412</b>	
<b>Power</b>	Power Adapter Voltage	Input: 110-240V/AC 50-60Hz
	The maximum power supply machine	60W
<b>Protection level</b>	Mould	+ -4KV
	Differential mode	+ -1KV
<b>Network Connector</b>	Network Port	6-PORT 10/100M SWITCH WITH 4-PORT POE WAN1/2 port : 10/100Mbps Ethernet WAN port
	Transmission Distance	Extend switch is default OFF, state(1~4 port): 100m Extend switch is ON, state:(1~4 port): 200m WAN1/2 port: 100m
	Transmission Medium	Cat5/5e/6 standard network cable
<b>Network Switch</b>	Network Standard	IEEE802.3/10BASE-T Ethernet
		IEEE802.3u/100BASE-TX Ethernet
		IEEE802.3x Flow Control, IEEE802.3af
	Maximum Frame Size	1536 Bytes
	MAC address list	2K
	Backplane bandwidth	1Gbps
<b>Power Over Ethernet</b>	PoE Power Supply Type	End-Span(4/5+;7/8-)
	PoE Power Consumption	af,at Adaptive (every port)
<b>LED Status Indicator</b>	PoE Ethernet	When the PoE power supply is used, 1-4 LEDs are green
		When accessing Ethernet, ports 1-4 are yellow
<b>Environmental</b>	Working temperature	0°C~55°C
	Storage temperature	-40°C~70°C
	Working humidity	10%-90% non-condensing
	Storage humidity	5%-95% non-condensing
<b>Mechanical</b>	Dimension (L x W x H) mm	220*140*40
	Weight	1.1KG
	Material	SECC
	Color	Dark grey

<b>Stability</b>	MTBF	>30000h
------------------	------	---------