

# Longse



## SPECIFICATION

<b>Model</b>	<b>LS-RT2418</b>	
<b>Power</b>	Power Adapter Voltage	Input 100-240V/AC 50/60Hz
	The maximum power supply machine	370W
<b>Protection level</b>	Mould	+ -4KV
	Differential mode	+ -1KV
<b>Network Connector</b>	Network Port	1~24 port: :10/100Mbps PoE Ethernet port 25~28 port:10/100/1000Mbps WAN1~WAN4 port 4-PORT 1000m SFP1~SFP2
	Transmission Distance	1~24 port: Recommended distance is 100m
	Transmission Medium	Cat5/5e/6 standard network cable
<b>Network Switch</b>	Network Standard	IEEE802.3/10BASE-T Ethernet
		IEEE802.3u/100BASE-TX Ethernet
		IEEE802.3ab 1000BASE-T Ethernet
	Maximum Frame Size	1536 Bytes
	MAC address list	2K
	Backplane bandwidth	20Gbps
<b>Power Over Ethernet</b>	PoE Power Supply Type	End-Span(4/5+;7/8-)
	PoE Power Consumption	at, (every port)
<b>LED Status Indicator</b>	POE Ethernet	POE: 24 green light indicates that the POE is power on
		Ethernet: 24 yellow light indicates that the Ethernet Link and Act
<b>Environmental</b>	Working temperature	0℃~50℃
	Working humidity	0%-90% non-condensing
	Storage temperature	-40℃~85℃
	Storage Humidity	0%-90% RH non-condensing
<b>Mechanical</b>	Dimension (L x W x H) mm	441*300*44
	Weight	5.3KG
	Material	SECC
	Color	Dark gray
<b>Stability</b>	MTBF	> 30000h