



## SPECIFICATION

<b>Model NO.</b>	<b>P4A</b>
<b>Camera</b>	
Image Sensor	1/3" Progressive Scan CMOS
Resolution	4MP
Effective Pixels	2560(H)*1440(V)
Compression	H.264/H.265
Electronic Shutter Time	Auto (1/1.5s~1/30000s)
Minimum Illumination	0.01 Lux
S/N Ratio	47dB
Scanning System	Progressive
Video Output	Wireless network
Reset Button	Yes
<b>PTZ</b>	
Horizontal Rotation Range	N/A
Tilt Rotation Range	N/A
Guard Points	N/A
<b>LENS Type</b>	
Focus Length	2.97mm F1.6
Focus Control	Fixed
Lens Type	Fixed
Pixels	4M Pixels
<b>Night Vision</b>	
Infrared LED	14 x 2PCS + 14 x 2PCS White light
Infrared Distance	7M
IR Status	AGC auto control
IR Power On	Auto Control
<b>Network</b>	
Ethernet	N/A
Protocol	TCP/IP、UDP/IP、DHCP、RTMP、MUTP
ONVIF	N/A
P2P	Support
4G	N/A
POE	N/A
Main Stream 1	2560*1440@15fps
Main Stream 2	N/A
Main Stream 3	N/A
Sub Stream 1	1280*720@15fps
Sub Stream 2	N/A
Sub Stream 3	N/A
Tri Stream	N/A
IE Brower	N/A
Smart Phone	support
<b>Wireless</b>	
Antena	3dbi
Hotspot	N/A
Wi-Fi	Wi-Fi(IEEE802.11b/g/n)
WIFI Range	No obstacles 100m Max.
<b>Camera Features</b>	
Day/Night	Color/ B&W (IR-CUT )
Image Config	YES
Corridor Pattern	N/A
ROI	N/A
Defog Mode	N/A
BLC	Support
HDR	N/A
3DNR	Support
DWDR	WDR
Motion Detection	Support
Privacy Masking	N/A
Recording Mode	SDcard
Language	Simplified Chinese, English, Japanese, German, Russian, French, Italian, Spanish
<b>Function</b>	
Audio	2-Way Audio
Alarm	Motion Detection、PIR human body infrared detection
SD Card Slot	Support Max 128G
<b>General</b>	
Housing	plastic,IP65
Bracket	Support
IR Cut Filter	YES
Power	DC 5V/1.5A or Battery(9000mAh)
Operation Temperature	-10° ~ 45°C /10% ~ 80% (no condensation)
Storage Temperature	-20°C ~ 60° /0% ~ 90% (no condensation)
Size	135 mm(L) × 75.2 mm(W) × 82.4 mm(H)