## Longse



| SPECIFICATION          |  |
|------------------------|--|
| Model NO.              | CMSDHTC500FPEW-ECO   |
| Video Output Mode      | AHD/TVI: 5M@20fps/1 <mark>2.5f</mark> ps, 4M@ <mark>30fps</mark> /25f <mark>ps/15fps, 2M</mark> @30fps/25fps; CVI:<br>4M@30fps/25fps, 2M <mark>@30</mark> fps/25fps;C <mark>VBS</mark> |
| Camera                 |  |
| Image Sensor           | 1/3" CMOS Sensor   |
| Image Resolution       | 5M:2592*1944 4M:2560*1440 2M:1920*1080   |
| TV System              | PAL/NTSC   |
| Electronic Shutter     | Auto   |
| Minimun Illumination   | Color : 0.03 lux@F2.0, 0 Lux with white light  |
| Scanning System        | Progressive Scan   |
| Lens                   |  |
| Focus Length           | 3.6mm  |
| Focus Control          | Fixed  |
| Lens Type              | Fixed  |
| Night Vision           |  |
| IR Cut Filter          | YES  |
| Infrared LED           | NO,Suport Warm white (4000K)   |
| Light Distance         | up to 25m  |
| IR Status              | AGC auto control   |
| <b>Camera Features</b> |  |

| Starlight             | N/A                                      |  |
|-----------------------|--|--|
| Day/Night             | Color                                    |  |
| OSD Menu              | YES                                      |  |
| WDR                   | DWDR                                     |  |
| ИТС                   | YES                                      |  |
| Noise Reduction       | DNR                                      |  |
| Coaxial Audio         | YES(only TVI )                           |  |
| White Balance         | AUTO / MANUAL                            |  |
| Gain Control          | AUTO                                     |  |
| General               |  |  |
| Housing               | Eyeball: Metal Cover&Base: Plastic, IP65 |  |
| Bracket               | NO                                       |  |
| Operation Temperature | -30°C ∽+50°C RH95% Max                   |  |
| Storage Temperature   | -20℃ ~ +60℃ RH95% Max                    |  |
| Power Source          | DC12V±10%, 500mA                         |  |
| Dimension             | ⊄ 107 x 88.34(H)mm                       |  |
| Weight                | 400g                                     |  |