



SPECIFICATION

| | |
|------------------------|---|
| Model NO. | CPSAHTC500FPEW-ECO |
| Video Output Mode | AHD/TVI: 5M@20fps/12.5fps, 4M@30fps/25fps/15fps, 2M@30fps/25fps; CVI: 4M@30fps/25fps, 2M@30fps/25fps;CVBS |
| Camera | |
| Image Sensor | 1/3" CMOS Sensor |
| Image Resolution | 5M:2592*1944 4M:2560*1440 2M:1920*1080 |
| TV System | PAL/NTSC |
| Electronic Shutter | Auto |
| Minimum Illumination | Color : 0.03 lux@F2.0, 0 Lux with white light |
| Scanning System | Progressive Scan |
| Lens | |
| Focus Length | 3.6mm |
| Focus Control | Fixed |
| Lens Type | Fixed |
| Night Vision | |
| IR Cut Filter | YES |
| Infrared LED | NO, Support Warm white (4000K) |
| Light Distance | up to 20m |
| IR Status | AGC auto control |
| Camera Features | |

| | |
|-----------------|----------------|
| Starlight | N/A |
| Day/Night | Color |
| OSD Menu | YES |
| WDR | DWDR |
| UTC | YES |
| Noise Reduction | DNR |
| Coaxial Audio | YES(only TVI) |
| White Balance | AUTO / MANUAL |
| Gain Control | AUTO |

General

| | |
|-----------------------|-------------------------|
| Housing | Plastic |
| Bracket | YES |
| Operation Temperature | -10°C ~ +60°C RH95% Max |
| Storage Temperature | -20°C ~ +60°C RH95% Max |
| Power Source | DC12V±10%, 400mA |
| Dimension | φ83.9* 68.8mm |
| Weight | 156.2g |