

IR Status



BMSCHTC500ESLW
AHD: 8M@15fps, 5M@20fps/12.5fps, 4M/2M@30fps/25fps; CVI: 8M@15fps/12.5fps, 4M/2M@30fps/25fps TVI: 8M@15fps/12.5fps, 5M@20fps/12.5fps, 4M/2M@30fps/25fps; CVBS
1/2.8" SONY Starvis Back-illuminated CMOS sensor
8M: <mark>3840</mark> *2 <mark>160 5</mark> M:2592*1944 4M:2560*1440 2M:1920*1080
PAL/NTSC
Auto
Color: 0.003 lux@F1.6, 0 Lux with white light
Progressive Scan
3.6mm
Fixed
Fixed
YES
NO,Suport Warm white (4000K)
up to 25m

AGC Auto Control

Camera Features	
Starlight	N/A
Day/Night	Color
OSD Menu	YES
WDR	120dB
итс	YES
Noise Reduction	3DNR
Coaxial Audio	N/A
White Balance	AUTO / MANUAL
Gain Control	AUTO
General	
Housing	Metal, IP67
Bracket	YES
Operation Temperature	-10°C ~ +60°C RH95% Max
Storage Temperature	-20°C ~ +60°C RH95% Max
Power Source	DC12V±10%, 450mA
Dimension	169(W) x 67.5(H) x 70(D)mm
Weight	500g