

Longse



SPECIFICATION

| | | |
|----------------------|---|----------------|
| Model NO. | BMSCHTC500FKEW | BMSCTHC500FKEW |
| Video Output Mode | AHD: 8M@15fps, 5M@20fps/12.5fps, 4M@30fps/25fps/15fps, 2M@30fps/25fps; TVI: 8M@15fps/12.5fps, 5M@20fps/12.5fps, 4M@30fps/25fps/15fps, 2M@30fps/25fps; CVI: 8M@15fps/12.5fps, 4M/2M@30fps/25fps; CVBS | |
| Camera | | |
| Image Sensor | 1/2.5" CMOS sensor | |
| Image Resolution | 8M:3840*2160 5M:2592*1944 4M:2560*1440 2M:1920*1080 | |
| TV System | PAL/NTSC | |
| Electronic Shutter | Auto | |
| Minimum Illumination | Color : 0.03 lux@F2.0, 0 Lux with white light | |
| Scanning System | Progressive Scan | |
| Lens | | |
| Focus Length | 3.6mm | |
| Focus Control | Fixed | |
| Lens Type | Fixed | |
| Night Vision | | |
| IR Cut Filter | YES | |
| Infrared LED | NO, Support Warm white (4000K) | |
| Light Distance | up to 25m | |
| IR Status | AGC Auto Control | |

Camera Features

| | |
|-----------------|----------------|
| Starlight | N/A |
| Day/Night | Color |
| OSD Menu | YES |
| WDR | DWDR |
| UTC | YES |
| Noise Reduction | DNR |
| Coaxial Audio | YES(only TVI) |
| White Balance | AUTO / MANUAL |
| Gain Control | AUTO |

General

| | |
|-----------------------|----------------------------|
| Housing | Metal, IP67 |
| Bracket | YES |
| Operation Temperature | -10°C ~ +60°C RH95% Max |
| Storage Temperature | -20°C ~ +60°C RH95% Max |
| Power Source | DC12V±10%, 450mA |
| Dimension | 169(W) x 67.5(H) x 70(D)mm |
| Weight | 500g |