Longse



| SPECIFICATION | |
|----------------------|--|
| Model NO. | BMSFHTC200FPEW BMSFTHC200FPEW |
| Video Output Mode | AHD/TVI: 5M@20fps/1 <mark>2.5fps</mark> , 4M@ <mark>30fps/</mark> 25fps/15fps, 2M@30fps/25fps; CV 4M@30fps/25fps, 2M@30fps/25fps;CVBS |
| Camera | |
| Image Sensor | 1/3" CMOS Sensor |
| Image Resolution | 5M:2592*1944 4M:2560*1440 2M:1920*1080 |
| TV System | PAL/NTSC |
| Electronic Shutter | Auto |
| Minimun Illumination | Color : 0.03 lux@F2.0, 0 Lux with white light |
| Scanning System | Progressive Scan |
| Lens | |
| Focus Length | 3.6mm |
| Focus Control | Fixed |
| Lens Type | Fixed |
| Night Vision | · |
| IR Cut Filter | YES |
| Infrared LED | NO,Suport Warm white (4000K) |
| Light Distance | up to 25m |
| IR Status | AGC Auto Control |

| Starlight | N/A | |
|-----------------------|------------------------|--|
| Day/Night | Color | |
| OSD Menu | YES | |
| WDR | DWDR | |
| υтс | YES | |
| Noise Reduction | DNR | |
| Coaxial Audio | YES(only TVI) | |
| White Balance | AUTO / MANUAL | |
| Gain Control | AUTO | |
| General | | |
| Housing | Metal, IP67 | |
| Bracket | YES | |
| Operation Temperature | -10℃ ~ +60℃ RH95% Max | |
| Storage Temperature | -20℃ ~ +60℃ RH95% Max | |
| Power Source | DC12V±10%, 500mA | |
| Dimension | 71.13 x65.62x174.95 mm | |
| Weight | 605g | |