



SPECIFICATION		
Model NO.	BMMBHTC5005XESLW	BMMBTHC5005XESLW
Video Output Mode	AHD: 8M@15fps, 5M@20fps/12.5fps, 4M/2M@30fps/25fps; CVI: 8M@15fps/12.5fps, 4M/2M@30fps/25fps TVI: 8M@15fps/12.5fps, 5M@20fps/12.5fps, 4M/2M@30fps/25fps; CVBS	
Camera		
Image Sensor	1/2.8" SONY Starvis Back-illuminated CMOS sensor	
Image Resolution	8M:3840*2160 5M:2592*1944 4M:2560*1440 2M:1920*1080	
TV System	PAL/NTSC	
Electronic Shutter	Auto	
Minimum Illumination	Color : 0.003 lux@F1.6, 0 Lux with white light	
Scanning System	Progressive Scan	
Lens		
Focus Length	2.7-13.5mm Motor Zoom	
Focus Control	Auto	
Lens Type	Auto	
Night Vision		
IR Cut Filter	N/A	
Infrared LED	NO, Support Warm white (4000K)	
Light Distance	40m	
IR Status	AGC auto control	
Camera Features		
Starlight	N/A	
Day/Night	Color	
OSD Menu	YES	
WDR	120dB	
UTC	YES	
Noise Reduction	3DNR	
Coaxial Audio	N/A	
White Balance	AUTO / MANUAL	
Gain Control	AUTO	

General	
Housing	Main Body:Metal Cover:Plastic, IP67
Bracket	YES
Operation Temperature	-10℃ ~ +60℃ RH95% Max
Storage Temperature	-20℃ ~ +60℃ RH95% Max
Power Source	DC12V±10%, 750mA
Dimension	268(W) x 95(H) x 88(D)mm
Weight	1.5Kg

LONGSEE