



SPECIFICATION

Model NO.	BMMBHTC500ESLW	BMMBTHC500ESLW
Video Output Mode	AHD: 8M@15fps, 5M@20fps/12.5fps, 4M/2M@30fps/25fps; CVI: 8M@15fps/12.5fps, 4M/2M@30fps/25fps TVI: 8M@15fps/12.5fps, 5M@20fps/12.5fps, 4M/2M@30fps/25fps; CVBS	

Camera

Image Sensor	1/2.8" SONY Starvis Back-illuminated CMOS sensor
Image Resolution	8M:3840*2160 5M:2592*1944 4M:2560*1440 2M:1920*1080
TV System	PAL/NTSC
Electronic Shutter	Auto
Minimun Illumination	Color : 0.003 lux@F1.6, 0 Lux with white light
Scanning System	Progressive Scan

Lens

Focus Length	6mm
Focus Control	up to 40m
Lens Type	Fixed

Night Vision

IR Cut Filter	N/A
Infrared LED	NO, Suport Warm white (4000K)
Light Distance	40m
IR Status	AGC auto control

Camera Features

Starlight	N/A
Day/Night	Color
OSD Menu	YES
WDR	120dB
UTC	YES
Noise Reduction	3DNR
Coaxial Audio	N/A
White Balance	AUTO / MANUAL

Gain Control	AUTO
General	
Housing	Main Body:Metal Cover:Plastic, IP67
Bracket	YES
Operation Temperature	-10℃ ~ +60℃ RH95% Max
Storage Temperature	-20℃ ~ +60℃ RH95% Max
Power Source	DC12V±10%, 750mA
Dimension	268(W) x 95(H) x 88(D)mm
Weight	1.5Kg

LONGSEE