

# Longse



## SPECIFICATION

|                      |                                                                             |                |
|----------------------|-----------------------------------------------------------------------------|----------------|
| Model NO.            | BMSFHTC200ESHW                                                              | BMSFHTC200ESHW |
| Video Output Mode    | AHD/TVI: 5M@20fps/12.5fps, 4M@30fps, 2M@30fps; CVI: 4M@30fps, 2M@30fps;CVBS |                |
| Camera               |                                                                             |                |
| Image Sensor         | 1/2.8" SONY Starvis Back-illuminated CMOS sensor                            |                |
| Image Resolution     | 5M:2592*1944 4M:2560*1440 2M:1920*1080                                      |                |
| TV System            | PAL/NTSC                                                                    |                |
| Electronic Shutter   | Auto                                                                        |                |
| Minimum Illumination | Color : 0.001 lux@F1.6, 0 Lux with white light                              |                |
| Scanning System      | Progressive Scan                                                            |                |
| Lens                 |                                                                             |                |
| Focus Length         | 3.6mm                                                                       |                |
| Focus Control        | Fixed                                                                       |                |
| Lens Type            | Fixed                                                                       |                |
| Night Vision         |                                                                             |                |
| IR Cut Filter        | N/A                                                                         |                |
| Infrared LED         | NO, Support Warm white (4000K)                                              |                |
| Light Distance       | 25m                                                                         |                |
| IR Status            | AGC auto control                                                            |                |
| Camera Features      |                                                                             |                |

|                 |               |
|-----------------|---------------|
| Starlight       | YES           |
| Day/Night       | Color         |
| OSD Menu        | YES           |
| WDR             | 120dB         |
| UTC             | YES           |
| Noise Reduction | AI-DNR        |
| Coaxial Audio   | N/A           |
| White Balance   | AUTO / MANUAL |
| Gain Control    | AUTO          |

**General**

|                       |                        |
|-----------------------|------------------------|
| Housing               | Metal, IP67            |
| Bracket               | YES                    |
| Operation Temperature | -10℃ ~ +60℃ RH95% Max  |
| Storage Temperature   | -20℃ ~ +60℃ RH95% Max  |
| Power Source          | DC12V±10%, 500mA       |
| Dimension             | 71.13 x65.62x174.95 mm |
| Weight                | 605g                   |