



## SPECIFICATION

|                   |                                                                                                                                                                        |                  |
|-------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------|
| Model NO.         | CMLEHTC5005XESLW                                                                                                                                                       | CMLETHC5005XESLW |
| Video Output Mode | AHD: 8M@15fps, 5M@20fps/12.5fps, 4M/2M@30fps/25fps;<br>CVI: 8M@15fps/12.5fps, 4M/2M@30fps/25fps<br>TVI: 8M@15fps/12.5fps, 5M@20fps/12.5fps, 4M/2M@30fps/25fps;<br>CVBS |                  |

## Camera

|                      |                                                     |
|----------------------|-----------------------------------------------------|
| Image Sensor         | 1/2.8" SONY Starvis Back-illuminated CMOS sensor    |
| Image Resolution     | 8M:3840*2160 5M:2592*1944 4M:2560*1440 2M:1920*1080 |
| TV System            | PAL/NTSC                                            |
| Electronic Shutter   | Auto                                                |
| Minimum Illumination | Color : 0.003 lux@F1.6, 0 Lux with white light      |
| Scanning System      | Progressive Scan                                    |

## Lens

|               |                       |
|---------------|-----------------------|
| Focus Length  | 2.7-13.5mm Motor Zoom |
| Focus Control | Auto                  |
| Lens Type     | Auto                  |

## Night Vision

|                |                                |
|----------------|--------------------------------|
| IR Cut Filter  | N/A                            |
| Infrared LED   | NO, Support Warm white (4000K) |
| Light Distance | up to 25m                      |
| IR Status      | AGC Auto Control               |

## Camera Features

|                       |                       |
|-----------------------|-----------------------|
| Starlight             | N/A                   |
| Day/Night             | Color                 |
| OSD Menu              | YES                   |
| WDR                   | 120dB                 |
| UTC                   | YES                   |
| Noise Reduction       | 3DNR                  |
| Coaxial Audio         | N/A                   |
| White Balance         | AUTO / MANUAL         |
| Gain Control          | AUTO                  |
| <b>General</b>        |                       |
| Housing               | Metal ,IP67           |
| Bracket               | Optional              |
| Operation Temperature | -10℃ ~ +60℃ RH95% Max |
| Storage Temperature   | -20℃ ~ +60℃ RH95% Max |
| Power Source          | DC12V±10%, 500mA      |
| Dimension             | φ115 x113(H) mm       |
| Weight                | 800g                  |