



## SPECIFICATION

Model NO.	CMLEHD400ESL
Video Output Mode	EX-SDI: 8M@15fps, 4M/2M@30fps/25fps; HD-SDI: 2M@30fps/25fps; AHD/TVI: 5M@20fps/12.5fps, 4M/2M@30fps/25fps; CVI: 4M/2M@30fps/25fps;CVBS
<b>Camera</b>	
Image Sensor	1/2.8" SONY Starvis Back-illuminated CMOS sensor
Image Resolution	8M:3840*2160 5M:2592*1944 4M:2560*1440 2M:1920*1080
TV System	PAL/NTSC
Electronic Shutter	Auto
Minimum Illumination	Color : 0.003 lux@F1.6, AGC ON; B/W : 0 lux with IR
Scanning System	Progressive Scan
<b>Lens</b>	
Focus Length	6mm
Focus Control	Fixed
Lens Type	Fixed
<b>Night Vision</b>	
IR Cut Filter	YES
Infrared LED	42μ x 2PCS
Infrared Distance	25M
IR Status	AGC Auto Control
<b>Camera Features</b>	

Starlight	N/A
Day/Night	YES
OSD Menu	YES
WDR	120dB
UTC	YES
Noise Reduction	3DNR
Coaxial Audio	N/A
White Balance	AUTO / MANUAL
Gain Control	AUTO

## **General**

Housing	Metal ,IP67
Bracket	Optional
Operation Temperature	-10°C ~ +60°C RH95% Max
Storage Temperature	-20°C ~ +60°C RH95% Max
Power Source	DC12V±10%, 500mA
Dimension	φ115 x113(H) mm
Weight	800g