



## SPECIFICATION

|                        |  |
|------------------------|--|
| Model NO.              | CMLETE200SH  |
| Video Output Mode      | AHD/TVI: 5M@20fps/12.5fps, 4M@30fps, 2M@30fps; CVI: 4M@30fps, 2M@30fps; EX-SDI: 4M/2M@30fps/25fps, 2M@60fps/50fps, 2M@30fps/25fps, 720P@60fps/50fps, 720 |
| <b>Camera</b>          |  |
| Image Sensor           | 1/2.8" SONY Starvis Back-illuminated CMOS Sensor   |
| Image Resolution       | 5M:2592*1944 4M:2560*1440 2M:1920*1080   |
| TV System              | PAL/NTSC   |
| Electronic Shutter     | Auto   |
| Minimum Illumination   | Color : 0.001 lux@F1.6, AGC ON; B/W : 0 lux with IR  |
| Scanning System        | Progressive Scan   |
| <b>Lens</b>            |  |
| Focus Length           | 6mm  |
| Focus Control          | Fixed  |
| Lens Type              | Fixed  |
| <b>Night Vision</b>    |  |
| IR Cut Filter          | YES  |
| Infrared LED           | 42μ x 2PCS   |
| Infrared Distance      | 25M  |
| IR Status              | AGC Auto Control   |
| <b>Camera Features</b> |  |

|                 |               |
|-----------------|---------------|
| Starlight       | YES           |
| Day/Night       | YES           |
| OSD Menu        | YES           |
| WDR             | 120dB         |
| UTC             | YES           |
| Noise Reduction | AI-DNR        |
| Coaxial Audio   | N/A           |
| White Balance   | AUTO / MANUAL |
| Gain Control    | AUTO          |

## **General**

|                       |                         |
|-----------------------|-------------------------|
| Housing               | Metal ,IP67             |
| Bracket               | Optional                |
| Operation Temperature | -10°C ~ +60°C RH95% Max |
| Storage Temperature   | -20°C ~ +60°C RH95% Max |
| Power Source          | DC12V±10%, 500mA        |
| Dimension             | φ115 x113(H) mm         |
| Weight                | 800g                    |