

Longse



SPECIFICATION

| | |
|------------------------|--|
| Model NO. | CMSBTE200SH |
| Video Output Mode | AHD/TVI: 5M@20fps/12.5fps, 4M@30fps, 2M@30fps; CVI: 4M@30fps, 2M@30fps; EX-SDI: 4M/2M@30fps/25fps, 2M@60fps/50fps, 2M@30fps/25fps, 720P@60fps/50fps, 720 |
| Camera | |
| Image Sensor | 1/2.8" SONY Starvis Back-illuminated CMOS Sensor |
| Image Resolution | 5M:2592*1944 4M:2560*1440 2M:1920*1080 |
| TV System | PAL/NTSC |
| Electronic Shutter | Auto |
| Minimum Illumination | Color : 0.001 lux@F1.6, AGC ON; B/W : 0 lux with IR |
| Scanning System | Progressive Scan |
| Lens | |
| Focus Length | 3.6mm |
| Focus Control | Fixed |
| Lens Type | Fixed |
| Night Vision | |
| IR Cut Filter | YES |
| Infrared LED | 42μ x 2PCS |
| Infrared Distance | 25M |
| IR Status | AGC Auto Control |
| Camera Features | |

| | |
|-----------------|---------------|
| Starlight | YES |
| Day/Night | YES |
| OSD Menu | YES |
| WDR | 120dB |
| UTC | YES |
| Noise Reduction | AI-DNR |
| Coaxial Audio | N/A |
| White Balance | AUTO / MANUAL |
| Gain Control | AUTO |

General

| | |
|-----------------------|-------------------------|
| Housing | Metal, IP67 |
| Bracket | NO |
| Operation Temperature | -10°C ~ +60°C RH95% Max |
| Storage Temperature | -20°C ~ +60°C RH95% Max |
| Power Source | DC12V±10%, 500mA |
| Dimension | ∅ 96 x 91(H) mm |
| Weight | 600g |