



## SPECIFICATION

Model NO.	CMSDHD800ES
Video Output Mode	EX-SDI: 8M@15fps, 4M/2M@30fps/25fps; HD-SDI: 2M@30fps/25fps; AHD/TVI/CVI: 8M@15fps/12.5fps, 4M/2M@30fps/25fps; CVBS
<b>Camera</b>	
Image Sensor	1/2.8" SONY CMOS sensor
Image Resolution	8M:3840*2160 4M:2560*1440 2M:1920*1080
TV System	PAL/NTSC
Electronic Shutter	Auto
Minimum Illumination	Color : 0.01 lux@F1.6, AGC ON; B/W : 0 lux with IR
Scanning System	Progressive Scan
<b>Lens</b>	
Focus Length	3.6mm
Focus Control	Fixed
Lens Type	Fixed
<b>Night Vision</b>	
IR Cut Filter	YES
Infrared LED	20μ x 2PCS
Infrared Distance	25M
IR Status	AGC Auto Control
<b>Camera Features</b>	

Starlight	N/A
Day/Night	YES
OSD Menu	YES
WDR	120dB
UTC	YES
Noise Reduction	3DNR
Coaxial Audio	N/A
White Balance	AUTO / MANUAL
Gain Control	AUTO

## General

Housing	Cover&Base: Plastic Eyeball: Metal,IP65
Bracket	NO
Operation Temperature	-30°C ~ +50°C RH95% Max
Storage Temperature	-20°C ~ +60°C RH95% Max
Power Source	DC12V±10%, 500mA
Dimension	∅ 107x88.34(H)mm
Weight	400g