



SPECIFICATION

| | |
|------------------------|---|
| Model NO. | BMLAHD4005XESL |
| Video Output Mode | EX-SDI: 8M@15fps, 4M/2M@30fps/25fps; HD-SDI: 2M@30fps/25fps; AHD/TVI: 5M@20fps/12.5fps, 4M/2M@30fps/25fps; CVI: 4M/2M@30fps/25fps;CVBS |
| Camera | |
| Image Sensor | 1/2.8" SONY Starvis Back-illuminated CMOS sensor |
| Image Resolution | 8M:3840*2160 5M:2592*1944 4M:2560*1440 2M:1920*1080 |
| TV System | PAL/NTSC |
| Electronic Shutter | Auto |
| Minimum Illumination | Color : 0.003 lux@F1.6, AGC ON; B/W : 0 lux with IR |
| Scanning System | Progressive Scan |
| Lens | |
| Focus Length | 2.7-13.5mm |
| Focus Control | Auto |
| Lens Type | Motorized |
| Night Vision | |
| IR Cut Filter | YES |
| Infrared LED | 42μ x 6PCS |
| Infrared Distance | 60M |
| IR Status | AGC Auto Control |
| Camera Features | |
| Starlight | N/A |

| | |
|-----------------|---------------|
| Day/Night | YES |
| OSD Menu | YES |
| WDR | 120dB |
| UTC | YES |
| Noise Reduction | 3DNR |
| Coaxial Audio | N/A |
| White Balance | AUTO / MANUAL |
| Gain Control | AUTO |

General

| | |
|-----------------------|---------------------------------------|
| Housing | Main Body: Metal Cover: Plastic, IP67 |
| Bracket | YES |
| Operation Temperature | -10°C ~ +60°C RH95% Max |
| Storage Temperature | -20°C ~ +60°C RH95% Max |
| Power Source | DC12V±10%, 900mA |
| Dimension | 220(W) x 109(H) x 106(D)mm |
| Weight | 2.15Kgs |