



SPECIFICATION

| | |
|--------------------------|--|
| Model NO. | BPSGTHC500FKERC |
| Video Output Mode | AHD/TVI/CVI: 2M@30fps/25fps;CVBS |
| Camera | |
| Image Sensor | 1/2.5" CMOS sensor |
| Image Resolution | 5M:2592*1944 4M:2560*1440 2M:1920*1080 |
| TV System | PAL/NTSC |
| Electronic Shutter | Auto |
| Minimum Illumination | Color: 0.03 Lux@(F2.0, AGC ON), 0 Lux with white light, B/W: 0 Lux with IR |
| Scanning System | Progressive Scan |
| Lens | |
| Lens Type | Fixed focal lens, 2.8 mm and 4 mm optional |
| Focus Length | 2.8 mm and 4 mm |
| Focus Control | Fixed |
| Night Vision | |
| IR Cut Filter | YES |
| Infrared LED | 3PCS |
| Infrared Distance | 30M |
| IR Status | AGC auto control |
| Camera Features | |
| Starlight | N/A |
| Day/Night | YES/YES |
| OSD Menu | YES |
| WDR | DWDR |
| UTC | YES |
| Noise Reduction | 2DNR |
| Coaxial Audio | YES(Support TVI and CVI) |
| White Balance | AUTO / MANUAL |

| | |
|-----------------------|-----------------------------|
| Gain Control | AUTO |
| General | |
| Housing | Plastic, IP66 |
| Bracket | YES |
| Operation Temperature | -10°C ~ +50°C RH95% Max |
| Storage Temperature | -20°C ~ +60°C RH95% Max |
| Power Source | DC12V±10%, 900mA |
| Dimension | 69.8(W) X 69.8(H) X159(D)mm |
| Weight | 160g |

LONGSE