



## SPECIFICATION

|                      |  |             |
|----------------------|--|-------------|
| Model NO.            | CMLEHTC200F  | CMLETHC200F |
| Video Output Mode    | AHD/TVI/CVI: 2M@30fps/25fps;CVBS                   |             |
| <b>Camera</b>        |  |             |
| Image Sensor         | 1/3" CMOS Sensor                                   |             |
| Image Resolution     | 2M:1920*1080                                       |             |
| TV System            | PAL/NTSC   |             |
| Electronic Shutter   | Auto   |             |
| Minimum Illumination | Color : 0.01 lux@F2.0, AGC ON; B/W : 0 lux with IR |             |
| Scanning System      | Progressive Scan                                   |             |
| <b>Lens</b>          |  |             |
| Focus Length         | 6mm  |             |
| Focus Control        | Fixed  |             |
| Lens Type            | Fixed  |             |
| <b>Night Vision</b>  |  |             |
| IR Cut Filter        | YES  |             |
| Infrared LED         | 42μ x 2PCS   |             |
| Infrared Distance    | 25M  |             |

|                        |                         |
|------------------------|-------------------------|
| IR Status              | AGC Auto Control        |
| <b>Camera Features</b> |                         |
| Starlight              | N/A                     |
| Day/Night              | YES                     |
| OSD Menu               | YES                     |
| WDR                    | DWDR                    |
| UTC                    | YES                     |
| Noise Reduction        | 3DNR                    |
| Coaxial Audio          | N/A                     |
| White Balance          | AUTO / MANUAL           |
| Gain Control           | AUTO                    |
| <b>General</b>         |                         |
| Housing                | Metal ,IP67             |
| Bracket                | Optional                |
| Operation Temperature  | -10°C ~ +60°C RH95% Max |
| Storage Temperature    | -20°C ~ +60°C RH95% Max |
| Power Source           | DC12V±10%, 500mA        |
| Dimension              | φ115 x113(H) mm         |
| Weight                 | 800g                    |

Longdsee