

## **CMSA**

#### **AHD/TVI HD Camera**



# CMSAHTC500FKE CMSATHC500FKE

- AHD/TVI HD Dome
- 1/2.5" CMOS sensor
- 3.6mm Fixed Lens
- IR Distance Max. 25m

www.longse.com

Data Subject To Change Without Notice

Longse


Model NO.	СМЅАНТС500FKE	CMSATHC500FKE
Video Output Mode	AHD: 8M@15fps, 5M@20fps/12.5fps, 4M@30fps/25fps/15fps, 2M@30fps/25fps; TVI: 8M@15fps/12.5fps,5M@20fps/12.5fps,4M@30fps/25fps/15fps, 2M@30fps/25fps; CVI: 8M@15fps/12.5fps,4M/2M@30fps/25fps;CVBS	
Camera		
Image Sensor	1/2.5" CMOS sensor	
Image Resolution	8M:3840*2160 5M:2592*1944 4M:2560*1440 2M:1920*1080	
TV System	PAL/NTSC	
Electronic Shutter	Auto	
Minimun Illumination	Color : 0.03 lux@F2.0, AGC ON; B/W : 0 lux with IR	
Scanning System	Progressive Scan	
Lens		
Focus Length	3.6mm	
Focus Control	Fixed	
Lens Type	Fixed	
Night Vision		
IR Cut Filter	YES	
Infrared LED	42μ x 2PCS	
Infrared Distance	25M	
IR Status	AGC Auto Control	
Camera Features		
Starlight	N/A	
Day/Night	YES	
OSD Menu	YES	
WDR	DWDR	
итс	YES	
Noise Reduction	DNR	
Coaxial Audio	YES(only TVI )	
White Balance	AUTO / MANUAL	
Gain Control	АUTO	
General		
Housing	Eyeball: Metal Base: Plastic , IP67	
Bracket	NO	
Operation Temperature	-10°C ~ +60°C RH95% Max	
Storage Temperature	-20°C ~ +60°C RH95% Max	
Power Source	DC12V±10%, 500mA	
Dimension	⊄ 109 x 93(H) mm	
Weight	600g	




### **Technical Specifications**

Model	CMSA	
Material	Aluminum & SECC & PC	
Dimension(WxHxD)	Ф109 x 93mm	
Weight	single set 600g (with packaging 800g)	
Color	Sand Grain White	
Operating Temperature	e -20°C ~ +60°C	
Humidity	< 95% RH	
Optional accessories	B116, B320, B173, PC116-CMSA	

### **Dimensions** (mm)





www.longse.com

Data Subject To Change Without Notice