



Model NO. Video Output Mode	CMSDHTC500FKE	CMSDTHC500FKE
Video Output Mode	AUD. 0M@15fmc	İ
	AHD: 8M@15fps, 5M@20fps/12.5fps, 4M@30fps/25fps/15fps, 2M@30fps/25fps; TVI: 8M@15fps/12.5fps,5M@20fps/12.5fps,4M@30fps/25fps/15fps, 2M@30fps/25fps; CVI: 8M@15fps/12.5fps,4M/2M@30fps/25fps;CVBS	
Camera		
Image Sensor	1/2.5" CMOS sensor	
Image Resolution	8M:3840*2160 5M:2592*1944 4M:2560*1440 2M:192 <mark>0*1080</mark>	
TV System	PAL/NTSC	
Electronic Shutter	Auto	
Minimun Illumination	Color: 0.03 lux@F2.0, AGC ON; B/W: 0 lux with IR	
Scanning System	Progressive Scan	
Lens		
Focus Length	3.6mm	
Focus Control	Fixed	
Lens Type	Fixed	
Night Vision		
IR Cut Filter	YES	
Infrared LED	20μ × 2PCS	
Infrared Distance	25M	
IR Status	AGC Auto Control	
Camera Features		
Starlight	N/A	
Day/Night	YES	
OSD Menu	YES	
WDR	DWDR	
UTC	YES	
Noise Reduction	DNR	
Coaxial Audio	YES(only TVI )	
White Balance	AUTO / MANUAL	
Gain Control	АИТО	
General		
Housing	Cover&Base: Plastic Eyeball: Metal,IP65	
Bracket	NO	
Operation Temperature	-30°C ∽+50°C RH95% Max	
Storage Temperature	-20℃ ~ +60℃ RH95% Max	
Power Source	DC12V±10%, 500mA	
Dimension	₡ 107x88.34(H)mm	
Weight	400g	