



SPECIFICATION	
Model NO.	LIRDLAHTC500FKE LIRDLATHC500FKE
Video Output Mode	AHD: 8M@15fps, 5M@20fps/12.5fps, 4M@30fps/25fps/15fps, 2M@30fps/25fps; TVI: 8M@15fps/12.5fps,5M@20fps/12.5fps,4M@30fps/25fps/15fps, 2M@30fps/25fps CVI: 8M@15fps/12.5fps,4M/2M@30fps/25fps;CVBS
Camera	
Image Sensor	1/2.5" CMOS sensor
Image Resolution	8M:3 <mark>840</mark> *21 <mark>60 5M</mark> :2592*1944 4M:2560*1440 2M:1920*1080
TV System	PAL/NTSC
Electroni <mark>c Shut</mark> ter	Auto
Minimun Illumination	Color: 0.03 lux@F2.0, AGC ON; B/W: 0 lux with IR
Scanning System	Progressive Scan
Lens	·
Focus Length	3.6mm
Focus Control	Fixed
Lens Type	Fixed
Night Vision	•
IR Cut Filter	YES
Infrared LED	14μ x 18PCS
Infrared Distance	20M
IR Status	AGC Auto Control
Camera Features	<u>'</u>

Starlight	N/A	
Day/Night	YES	
OSD Menu	YES	
WDR	DWDR	
итс	YES	
Noise Reduction	DNR	
Coaxial Audio	YES(only TVI)	
White Balance	AUTO / MANUAL	
Gain Control	AUTO	
General		
Housing	Plastic	
Bracket	Optional	
Operation Temperature	-10°C ~ +60°C RH95% Max	
Storage Temperature	-20°C ~ +60°C RH95% Max	
Power Source	DC12V±10%, 550mA	
Dimension	⊄ 99(W) x 81(H)mm	
Weight	300g	