

LMDH

AHD/TVI HD Camera



LMDHHTC200FPE
LMDHTHC200FPE

- AHD/TVI HD Dome
- 1/3" CMOS Sensor
- 3.6mm Fixed Lens
- IR Distance Max. 15m

www.longse.com

Data Subject To Change Without Notice

| | | |
|------------------------|---|---------------|
| Model NO. | LMDHHTC200FPE | LMDHHTC200FPE |
| Video Output Mode | AHD/TVI: 5M@20fps/12.5fps, 4M@30fps/25fps/15fps, 2M@30fps/25fps; CVI: 4M@30fps/25fps, 2M@30fps/25fps;CVBS | |
| Camera | | |
| Image Sensor | 1/3" CMOS Sensor | |
| Image Resolution | 5M:2592*1944 4M:2560*1440 2M:1920*1080 | |
| TV System | PAL/NTSC | |
| Electronic Shutter | Auto | |
| Minimum Illumination | Color : 0.03 lux@F2.0, AGC ON; B/W : 0 lux with IR | |
| Scanning System | Progressive Scan | |
| Lens | | |
| Focus Length | 3.6mm | |
| Focus Control | Fixed | |
| Lens Type | Fixed | |
| Night Vision | | |
| IR Cut Filter | YES | |
| Infrared LED | 14μ x 12PCS | |
| Infrared Distance | 15M | |
| IR Status | AGC Auto Control | |
| Camera Features | | |
| Starlight | N/A | |
| Day/Night | YES | |
| OSD Menu | YES | |
| WDR | DWDR | |
| UTC | YES | |
| Noise Reduction | DNR | |
| Coaxial Audio | YES(only TVI) | |
| White Balance | AUTO / MANUAL | |
| Gain Control | AUTO | |
| General | | |
| Housing | Metal, IP67 | |
| Bracket | Optional | |
| Operation Temperature | -10℃ ~ +60℃ RH95% Max | |
| Storage Temperature | -20℃ ~ +60℃ RH95% Max | |
| Power Source | DC12V±10%, 450mA | |
| Dimension | ∅ 110 x 76(H) mm | |
| Weight | 450g | |

Technical Specifications

| | |
|-----------------------|-----------------------|
| Model | LMDH |
| Material | Aluminum & SECC & PC |
| Dimension(WxHxD) | Φ110 x 76mm |
| Weight | 450g (with packaging) |
| Color | Sand Grain White |
| Operating Temperature | -20°C ~ +60°C |
| Humidity | < 95% RH |
| Optional accessories | B173-01 |

Dimensions (mm)

