



SPECIFICATION			
Model NO.	LBP90HTC500FKE	LBP90THC500FKE	
Video Output Mode	AHD: 8M@15fps, 5M@20fps/12.5fps, 4M@30fps/25fps/15fps, 2M@30fps/25fps; TVI: 8M@15fps/12.5fps,5M@20fps/12.5fps,4M@30fps/25fps/15fps, 2M@30fps/25fps; CVI: 8M@15fps/12.5fps,4M/2M@30fps/25fps;CVBS		
Camera	, , , , , , , , , , , , , , , , , , , ,		
Image Sensor	1/2.5" CMOS sensor	1/2.5" CMOS sensor	
Image Resolution	8M:3840*21605M:2592*19444N	8M:3840*21605M:2592*19444M:2560*14402M:192 <mark>0*108</mark> 0	
TV System	PAL/NTSC		
Electronic Shutter	Auto		
Minimun Illumination	Color: 0.03 lux@F2.0, AGC ON; B/W: 0 lux with IR		
Scanning System	Progressive Scan		
Lens			
Focus Length	2.8-12mm		
Focus Control	Manual		
Lens Type	Varifocal		
Night Vision			
IR Cut Filter	YES		
Infrared LED	42μ x 6PCS		
Infrared Distance	60M	60M	
IR Status	AGC Auto Control		
Camera Features	3		
Starlight	N/A		
Day/Night	YES		
OSD Menu	YES		
WDR	DWDR		
итс	YES		
Noise Reduction	DNR		
Coaxial Audio	YES(only TVI )	YES(only TVI )	
White Balance	AUTO / MANUAL	AUTO / MANUAL	
Gain Control	AUTO	аито	
General			
Housing	Metal, IP67	Metal, IP67	
Bracket	YES	YES	
Operation Temperature	-10°C ~+60°C RH95% Max	-10 °C ~ +60 °C RH95% Max	
Storage Temperature	-20°C ~+60°C RH95% Max	-20°C ~ +60°C RH95% Max	
Power Source	DC12V±10%, 900mA		
Dimension	211(W) x 92(H) x 90(D)mm	211(W) x 92(H) x 90(D)mm	
Weight	1400g		