



SPECIFICATION	
Model NO.	BMLCKL8AD
Camera	
Image Sensor	1/2.8" SONY Starvis Back-illuminated CMOS sensor
Resolution	8MP
Effective Pixels	3864(H)*2192(V)
Compression	H.264/H.265/H.265+
Audio Compression	G711A/U,AAC,MP2L2
TV System	PAL/NTSC
Electronic Shutter Time	Auto: 1/3-1/100000Sec
Minimun Illumination	Color: 0.005 Lux@(F1.6, AGC ON), 0 Lux with white light, B/W: 0 Lux with IR
S/N Ratio	60dB
Scanning System	Progressive
Video Output	Network
Reset Button	Support
Lens	
Focal Length & FOV	2.8 mm, horizontal FOV 96°, vertical FOV 52°, diagonal FOV 114° 4 mm, horizontal FOV 84°, vertical FOV 48°, diagonal FOV 97°
Lens Type	Fixed focal lens, 2.8 and 4 mm optional
Focus Control	Fixed
Aperture	F1.6
Pixels	8MP
Night Vision	
Supplement Light	42μ x 2PCS(Warm light LED 4000K)
Supplement Light Distance	IR:50m, Warm light:40m
Supplement Light Status	Auto Control
Supplement Light Power On	Smart, Manual & Timed mode
Network	
Ethernet	RJ-45 (10/100Base-T)
Wireless	N/A
Protocol	TCP/IP,IPv4/v6, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, NTP, SMTP, UDP, SNMP,Qos,802.1x
ONVIF	Support ONVIF 19.12(Profile S/T)
P2P	YES
POE	Internal, Support IEEE 802.3af
Video Delay	0.3S (Within the Lan)
Main Stream 1	3840*2160@20fps
Main Stream 2	2560*1440@20fps
Main Stream 3	1920*1080@20fps 1280*720@20fps
Sub Stream 1	1280*720@20fps

Sub Stream 3 Tri Stream IE Brower Smart Phone Al Function Intelligent Analysis	N/A N/A IE8-11, Google Chrome, Firefox , Mac Safari iPhone, Android
IE Brower Smart Phone Al Function Intelligent Analysis	IE8-11, Google Chrome, Firefox , Mac Safari iPhone, Android
Smart Phone Al Function Intelligent Analysis	iPhone, Android
Al Function Intelligent Analysis	
Intelligent Analysis	
	Intrusion Detetion(based on human and Vehicle Detection), Line Cross Detetion(based on human and Vehicle Detection), Loiter Detetion(based on human detection), People Gather Detecion(based on human detection), Motion detection based on human detection, Enter Area(based on human and Vehicle Detection), Leave Area(based on human and vehicle Detection)
Camera Features	
Day/Night	Color/ B&W (IR-CUT)
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR, White Balance, Anti Flicker, Video Tampering, HLC
Full Color	Support
Corridor Pattern	Support
Defog Mode	N/A
ROI	Support
BLC	Support
WDR	120dB
Motion Detection	Support(support enable the detection based on human movement only)
Privacy Masking	3 Rectangular Zone
Recording Mode	NVR/CMS/Web
Language	Chinese Simplified, Chinese Traditional, English, Korean, Polish, French, Japanese, Spanish, Portuguese, Italian, Hebrew, Ukrainian, Arabic, Vietnamese, Tl
Interface	Hungarian
Audio	Default: Built in Mic+Built in Speaker
Alarm	Default: Alarm I/O
Alarm SD Card Slot	Default: Alarm I/O External, Support Max 512GB
SD Card Slot	External, Support Max 512GB
SD Card Slot RS485	
SD Card Slot RS485 General	External, Support Max 512GB N/A
SD Card Slot RS485 General Housing	External, Support Max 512GB N/A Metal,IP67
SD Card Slot RS485 General Housing Anti-cut Bracket	External, Support Max 512GB N/A
SD Card Slot RS485 General Housing Anti-cut Bracket IR Cut Filter	External, Support Max 512GB N/A Metal,IP67 NO
SD Card Slot	External, Support Max 512GB N/A Metal,IP67 NO YES
SD Card Slot RS485 General Housing Anti-cut Bracket IR Cut Filter Operation Temperature	External, Support Max 512GB N/A Metal,IP67 NO YES -30°C ~+60°C RH95% Max
SD Card Slot RS485 General Housing Anti-cut Bracket IR Cut Filter Operation Temperature Storage Temperature	External, Support Max 512GB N/A Metal,IP67 NO YES -30°C ~+60°C RH95% Max -20°C ~+60°C RH95% Max