

8MP AI ISP Full Color IP Camera

CMSETL8RC



- Built-in Mic
- External SD Card Slot, Alarm I/O
- Face Detection
- Line Crossing Count
- Illegal Parking (based on vehicle shape and license plates)
- License Plate Detection
- Abandoned Object Detection & Removed Object Detection
- Heat Map



Camera

| | |
|-------------------------|---|
| Image Sensor | 1/2.8" SONY Starvis Back-illuminated CMOS sensor |
| Resolution | 8MP |
| Effective Pixels | 3864(H)*2192(V) |
| Compression | H.264/H.264+/H.265/H.265+ |
| Audio Compression | G711A/U,AAC,MP2L2 |
| TV System | PAL/NTSC |
| Electronic Shutter Time | Auto: 1/3-1/100000Sec |
| Minimun Illumination | Color: 0.005 Lux@(F1.6, AGC ON), 0 Lux with white light, B/W: 0 Lux with IR |
| S/N Ratio | 60dB |
| Scanning System | Progressive |
| Video Output | Network |
| Reset Button | Optional |

Lens

| | |
|--------------------|--|
| Focal Length & FOV | 2.8 mm, horizontal FOV 96°, vertical FOV 52°, diagonal FOV 114° 4 mm, horizontal FOV 84°, vertical FOV 48°, diagonal FOV 97° 6 mm, horizontal FOV 4°, vertical FOV 25°, diagonal FOV 51° |
| Lens Type | Fixed focal lens, 2.8, 4 and 6 mm optional |
| Focus Control | Fixed |
| Aperture | F1.6 |
| Pixels | 8MP |

Night Vision

| | |
|---------------------------|----------------------------|
| Supplement Light | IR: 2PCS, Warm light: 2PCS |
| Supplement Light Distance | IR: 40m, Warm light: 30m |
| Supplement Light Status | Auto Control |
| Supplement Light Power On | Smart, Manual & Timed mode |

Network

| | |
|---------------|---|
| Ethernet | RJ-45 (10/100Base-T) |
| Wireless | N/A |
| Protocol | TCP/IP, IPv4/v6, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTMP, RTCP, PPPoE, NTP, SMTP, UDP, SNMP, Qos, 802.1x |
| ONVIF | Support ONVIF 24.12(Profile S/T/G/M) |
| P2P | YES |
| POE | Internal, Support IEEE 802.3af |
| Video Delay | 300ms (Within the Lan) |
| Main Stream 1 | 3840*2160@30fps 2560*1440@30fps |
| Main Stream 2 | 1920*1080@30fps |
| Main Stream 3 | 1280*720@30fps |
| Sub Stream 1 | 1280*720@30fps |
| Sub Stream 2 | 720*480@30fps |

| | |
|--------------|--|
| Sub Stream 3 | N/A |
| Tri Stream | 720*480@30fps 352*288@30fps |
| IE Brower | Microsoft Edge, IE11, Google Chrome, Firefox, Mac Safari |
| Smart Phone | iPhone, Android |

AI Function

| | |
|----------------------|--|
| Intelligent Analysis | Intrusion Detection/Line Crossing Detection/Enter Area Detection/Leave Area Detection/Line Crossing Count(based on human and vehicle detection), Loitering Detection/People Gathering Detection(based on human detection), Motion Detection(supports the detection based on human and vehicle movement), Face Detection, Illegal Parking(based on vehicle shape and license plates), License Plate Detection, Abandoned Object Detection, Removed Object Detection, Heat Map |
|----------------------|--|

Camera Features

| | |
|------------------|---|
| Day/Night | Color/ B&W (IR-CUT) |
| Image Config | Saturation/Brightness/Contrast/Sharpness, Mirror, 3D NR, White Balance, Anti Flicker, Video Tampering, HLC, Scene Change Detection |
| Full Color | Support |
| Corridor Pattern | Support |
| Defog Mode | Support |
| ROI | Support |
| BLC | Support |
| WDR | 120dB |
| Motion Detection | Support(support enable the detection based on human and Vehicle movement) |
| Privacy Masking | 3 Rectangular Zone |
| Recording Mode | NVR/CMS/Web |
| Language | Chinese Simplified, Chinese Traditional, English, Korean, Polish, French, Japanese, Spanish, Portuguese, Italian, Hebrew, Ukrainian, Arabic, Vietnamese, Thai, Hungarian, Czech |


Interface

| | |
|--------------|---|
| Audio | Default: Built in Mic Option: Audio In Option: Audio I/O Option: Built in Mic+Built in Speaker |
| Alarm | N/A |
| SD Card Slot | Default: Without Option: External SD card slot (Max 512GB) |
| RS485 | N/A |

General

| | |
|-----------------------|-------------------------------|
| Housing | Metal, IP67 |
| Anti-cut Bracket | NO |
| IR Cut Filter | YES |
| Operation Temperature | -30°C ~ +60°C RH95% Max |
| Storage Temperature | -30°C ~ +60°C RH95% Max |
| Power Source | DC12V±10%, 500mA |
| Dimension | ∅ 125 x 90.2(H) mm |
| Weight (N.W./G.W.) | Approx. 508 g / Approx. 682 g |

Dimensions (mm)



Optional Accessories



B245
Side Bracket