



## SPECIFICATION

|                           |   |
|---------------------------|---|
| <b>Model NO.</b>          | <b>CMSCKL800WH</b>  |
| <b>Camera</b>             |   |
| Image Sensor              | 1/2.8" SONY Starvis Back-illuminated CMOS sensor  |
| Resolution                | 8MP   |
| Effective Pixels          | 3864(H)*2192(V)   |
| Compression               | H.264/H.265/H.264+/H.265+/JPEG/AVI  |
| Audio Compression         | G711A/U,AAC   |
| TV System                 | PAL/NTSC  |
| Electronic Shutter Time   | Auto: 1/3-1/100000Sec   |
| Minimum Illumination      | Color : 0.02 lux@F1.6, 0 Lux with white light   |
| S/N Ratio                 | 60dB  |
| Scanning System           | Progressive   |
| Video Output              | Network   |
| Reset Button              | Optional  |
| <b>Lens</b>               |   |
| Focal Length & FOV        | 2.8 mm, horizontal FOV 96°, vertical FOV 52°, diagonal FOV 114°<br>3.6 mm, horizontal FOV 84°, vertical FOV 48°, diagonal FOV 97°<br>6 mm, horizontal FOV 53°, vertical FOV 30°, diagonal FOV 60° |
| Lens Type                 | Fixed focal lens, 2.8, 3.6, and 6 mm optional   |
| Focus Control             | Fixed   |
| Aperture                  | F1.6  |
| Pixels                    | 8MP   |
| <b>Night Vision</b>       |   |
| Supplement Light          | No,Support Warm light LED 4000K, up to 25m  |
| Supplement Light Distance | N/A   |
| Supplement Light Status   | Auto Control  |
| Supplement Light Power On | Smart, Manual & Timed mode  |
| <b>Network</b>            |   |
| Ethernet                  | RJ-45 (10/100Base-T)  |
| Wireless                  | N/A   |
| Protocol                  | TCP/IP,IPv4/v6, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP ,PPPoE, NTP, SMTP, UDP, SNMP,Qos,802.1x  |
| ONVIF                     | Support ONVIF 19.12(Profile S/T/G)  |
| P2P                       | YES   |
| POE                       | Internal, Support IEEE 802.3af  |
| Video Delay               | 0.3S (Within the Lan)   |
| Main Stream 1             | 3840*2160@20fps   |

|               |   |
|---------------|---|
| Main Stream 2 | 2560*1440@20fps                             |
| Main Stream 3 | 1920*1080@20fps<br>1280*720@20fps           |
| Sub Stream 1  | 1280*720@20fps                              |
| Sub Stream 2  | 720*480@20fps                               |
| Sub Stream 3  | N/A   |
| Tri Stream    | N/A   |
| IE Brower     | IE8-11, Google Chrome, Firefox , Mac Safari |
| Smart Phone   | iPhone, Android                             |

## AI Function

|                      |   |
|----------------------|---|
| Intelligent Analysis | Intrusion Detetion(based on human and Vehicle Detection), Line Cross Detetion(based on human and Vehicle Detection), Loiter Detetion(based on human detection), People Gather Detecion(based on human detection), Motion detection based on human detection |
|----------------------|---|

## Camera Features

|                  |   |
|------------------|---|
| Day/Night        | Color   |
| Image Config     | Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, Anti Flicker, Video Tampering,HLC   |
| Full Color       | Support   |
| Corridor Pattern | Support   |
| Defog Mode       | N/A   |
| ROI              | Support   |
| BLC              | Support   |
| WDR              | Support   |
| Motion Detection | Support(support enable the detection based on human movement only)  |
| Privacy Masking  | 3 Rectangular Zone  |
| Recording Mode   | NVR/CMS/Web   |
| Language         | Chinese Simplified, Chinese Traditional, English, Russian, Korean, Polish, French, Japanese, Spanish, Portuguese, Italian, Hebrew, Ukrainian, Arabic, Vietnamese, Thai, Hungarian |

## Interface

|              |                                    |
|--------------|------------------------------------|
| Audio        | Optional 1 Built-in MIC            |
| Alarm        | N/A                                |
| SD Card Slot | Optional Internal, Support Max 1TB |
| RS485        | N/A                                |

## General

|                       |                              |
|-----------------------|------------------------------|
| Housing               | Metal ( Ring Plastic) , IP67 |
| Anti-cut Bracket      | NO                           |
| IR Cut Filter         | YES                          |
| Operation Temperature | -20℃ ~ +60℃ RH95% Max        |
| Storage Temperature   | -20℃ ~ +60℃ RH95% Max        |
| Power Source          | DC12V±10%, 1000mA            |
| Dimension             | φ126.8 x 93.8(H) mm          |
| Weight                | 630g                         |