



## SPECIFICATION

<b>Model NO.</b>	<b>LMBM36FW400W</b>
<b>Camera</b>	
Image Sensor	1/3" Progressive Scan CMOS Sensor
Resolution	4MP
Effective Pixels	2560(H)*1440(V)
Compression	H.264/H.264+/H.265/H.265+/JPEG/AVI
Audio Compression	G711A/U,AAC
TV System	PAL/NTSC
Electronic Shutter Time	Auto: 1/3-1/100000Sec
Minimum Illumination	Color: 0.01 Lux @ (F1.6, AGC ON)
S/N Ratio	60dB
Scanning System	Progressive
Video Output	Network
Reset Button	Support
<b>Lens</b>	
Focus Length	Board Lens 2.8mm/F2.0
Focus Control	Fixed
Lens Type	Fixed
Pixels	4Mp
<b>Night Vision</b>	
Infrared LED	N/A
Infrared Distance	N/A
IR Status	N/A
IR Power On	N/A
<b>Network</b>	
Ethernet	RJ-45 (10/100Base-T)
Wireless	Optional, Wi-Fi(IEEE802.11b/g/n),2.4Ghz,Antena:2.5dbi,WIFI Range:No obstacles 100m Max
Protocol	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, SMTP, UDP
ONVIF	Support ONVIF 1.9.12(Profile S/T/G)
P2P	YES
POE	Optional(External POE But Without Audio and Alarm Functions), Support IEEE 802.3af
Video Delay	0.3S (Within the Lan)
Main Stream 1	2688*1512@20fps
Main Stream 2	2560*1440@30fps
Main Stream 3	1920*1080@30fps 1280*720@30fps
Sub Stream 1	1280*720@30fps
Sub Stream 2	720*480@30fps
Sub Stream 3	N/A
Tri Stream	N/A
IE Brower	IE8-11, Google Chrome, Firefox , Mac Safari
Smart Phone	iPhone, Android
<b>AI Function</b>	
Intelligent Analysis	Intrusion Detetion,motion detection based on human detection
<b>Camera Features</b>	
Day/Night	Color
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, Anti Flicker, Video Tampering, HLC, Distortion
Full Color	Support
Corridor Pattern	Support
Defog Mode	Support
ROI	Support
BLC	Support
WDR	120dB
Motion Detection	Support(support enable the detection based on human movement only)
Privacy Masking	3 Rectangular Zone
Recording Mode	NVR/CMS/Web
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Arabic, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian,Nederlands,Czech, Vietnamese
<b>Interface</b>	
Audio	1 Built-in MIC,Optional Audio IN/OUT(3.5mm audio interface),N/A(Optional External POE)
Alarm	Optional 1 Channel Input
SD Card Slot	Support 512G Micro SD Card Slot
RS485	N/A
<b>General</b>	
Housing	Metal
Anti-cut Bracket	No
IR Cut Filter	No
Operation Temperature	-20℃ ~ +60℃ RH95% Max
Storage Temperature	-20℃ ~ +60℃ RH95% Max
Power Source	DC12V±10%, 350mA
Dimension	36(W) x 36(H) x33(D)mm
Weight	300g