



SPECIFICATION

Model	HT82GA	
Power	Power Adapter Voltage	Input: 110-240V/AC 50-60Hz
	The maximum power supply machine	120W(52V 2.3A)
Network Connector	Network Port	8*10/100mbps POE port 2*100/1000mbps UP Link port
	Transmission Distance	Extend switch is default OFF, state(1~4 port): 100m Extend switch is ON, state:(1~4 port): 250m WAN1/2 port: 100m
	Transmission Medium	Cat5/5e/6 standard network cable
Network Switch	Network Standard	IEEE802.3/10BASE-T Ethernet, IEEE802.3u/100BASE-TX Ethernet, IEEE802.3x Flow Control, IEEE802.3af, IEEE802.3at
	Forwarding Mode	Store and forward
	Forwarding Rate	100Mbps:14880pps, 1000Mbps:14800pps
	Network Medium	10/100BASE-TX:5 class and above non shielded twisted pair
	MAC address list	2K
	Backplane bandwidth	10Gbps
	PoE Standard	IEEE 802.3af, IEEE 802.3at
Power Over Ethernet	PoE Power Supply Type	End-Span(1/2+,3/6-)
	PoE Power Consumption	af,at Adaptive (every port)
	Port Function	Power priority mechanism, fast and forward, MAC automatic learning and aging IEEE802.3X Full-duplex and mode and backpressure for Half-duplex mode
LED Indicator	/	LINK/ACT.100Mbps;POE Status Indicator; Power indicator;Extender
Environmental	Working temperature	-10℃~55℃
	Storage Temperature	-40℃~85℃
	Humidity	5%-90% , non-condensing
Mechanical	Dimension (L x W x H) mm	270*180*44
	Weight	1.2kg