



SPECIFICATION

| Model | HT82GC | |
|---------------------|----------------------------------|---|
| Power | Power Adapter Voltage | Input: 110-240V/AC 50-60Hz |
| | The maximum power supply machine | 120W(52V 2.3A) |
| Network Connector | Network Port | 8*10/100mbps POE port 2*100/1000mbps UP Link port |
| | Transmission Distance | Extend switch is default OFF, state(1~4 port): 100m Extend switch is ON, state:(1~4 port): 250m WAN1/2 port: 100m |
| | Transmission Medium | Cat5/5e/6 standard network cable |
| Network Switch | Network Standard | IEEE802.3/10BASE-T Ethernet, IEEE802.3u/100BASE-TX Ethernet, IEEE802.3x Flow Control, IEEE802.3af, IEEE802.3at |
| | Forwarding Mode | Store and forward |
| | Forwarding Rate | 100Mbps:14880pps, 1000Mbps:14800pps |
| | Network Medium | 10/100BASE-TX:5 class and above non shielded twisted pair |
| | MAC address lis | 2K |
| | Backplane bandwidth | 10Gbps |
| | PoE Standard | IEEE 802.3af, IEEE 802.3at |
| Power Over Ethernet | PoE Power Supply Type | End-Span(1/2+,3/6-) |
| | PoE Power Consumption | af,at Adaptive (every port) |
| | Port Function | Power priority mechanism, fast and forward, MAC automatic learning and aging IEEE802.3X Full-duplex and mode and backpressure for Half-duplex mode |
| LED Indicator | / | LINK/ACT.100Mbps;POE Status Indicator; Power indicator;Extender |
| Environmental | Working temperature | -10°C~55°C |
| | Storage Temperature | -40°C~85°C |
| | Humidity | 5%-90% , non-condensing |
| Mechanical | Dimension (L x W x H) mm | 270*180*44 |
| | Weight | 1.2kg |