



SPECIFICATION

Model NO.	XVRT3004C4PD500W
Package	
XVR	1x XVR3004C1N
Camera	4 x TP1BTHC500FPEW-ECO
Cable	4x 18m BNC+DC Cable, 1 x 4CH Power Splitter Cable
Mouse	1xUSB 2.0 Mouse
Hard Disk	No
Adaptor	2 x DC12V2A Adaptor
Weight	
Camera Model	TP1BTHC500FPEW-ECO
Image Sensor	1/3" CMOS sensor
Image Resolution	5M:2592*1944 4M:2560*1440 2M:1920*1080
TV System	PAL/NTSC
Electronic Shutter	AUTO
Minimum Illumination	Color : 0.03 lux@F2.0, 0 Lux with white light
Scanning System	Progressive Scan
Lens	
Focus Length	3.6mm
Focus Control	Fixed
Lens Type	Fixed
Night Vision	
IR Cut Filter	NO
Infrared LED	NO, Suport Warm white 32μ x 2PCS(4000K)
Infrared Distance	25M
IR Status	AGC auto control
Camera Features	
Starlight	N/A
Day/Night	Color
OSD Menu	YES
WDR	DWDR
UTC	YES
Noise Reduction	DNR
Coaxial Audio	YES
White Balance	AUTO / MANUAL
Gain Control	AUTO

General

Housing	Plastic
Bracket	NO
Operation Temperature	-10℃ ~ +60℃ RH95% Max
Storage Temperature	-20℃ ~ +60℃ RH95% Max
Power Source	DC12V±10%, 550mA
Dimension	φ90.6* 79.5mm
Weight	171.5g
Model	XVR3004C1N

System

Main Processor	MC6630
Operating System	Embedded LINUX

Video

Input	Analog: 4*(TVI/AHD: 5M@12fps; AHD/TVI/CVI: 4M@15fps; AHD/TVI/CVI: 1080P/720P@30fps; Analog: 960H) Analog+Network: 2*Analog(5MP)+4*network(MAX 5MP) Network: 9*5MP/4MP/3MP/1080P/960P/720P(Total incoming bandwidth ≤48M)
Input	4CH BNC
Signal Type	Analog/AHD/CVI/TVI 2.0/TVI 3.0/Network
Output	1HD,1 VGA

Audio

Input	1 ChannelRCA,support AOC
Two-way Audio	NO
Output	1 Channel RCA

Alarm

Sensor Input	NO
Output	NO
Motion Detection	4 Channel(max 9 Channel in pure network mode)
Trigger Events	Recording, Email, Screen tips, Push notifications(motion detection)
Email Alarm	Send Image to The Designated E-mail

AI Function

Human Detection	YES
-----------------	-----

PTZ

Interface	NO
Protocol	Coaxial Control
Baud Rate	NO
Address	NO

Display

VGA	Resolution:1920 × 1080P, 1280 × 1024 , 1280 × 720,1024 × 768
HD Output	Resolution:1920 × 1080P, 1280 × 1024 , 1280 × 720,1024 × 768
Display Split	1/4/8/9
Privacy Masking	3 Rectangular Zones (Each camera)
OSD	Camera title, Time, Video loss, Motion detection, Recording

Recording

Video Compression	H.265/H.264
Audio Compression	G.711U/G.711A
Resolution	5MP_Lite(1280×1952),4MP_Lite(1280×1440),1080N(960×1080),720P(1280×720),960H(960×480)
Video Quality	Lowest/Low/Ordinary/Good/Better/Best

Record Rate	Analog: PAL: 5MP_Lite(1296×1944 4*12fps),4MP_Lite(1280×1440 4*15fps),1080N(960×1080 4*25fps),720P(1280×720 4*25fps), 960H(960×480 4*25fps) NTSC:5MP_Lite(1296×1944 4*12fps),4MP_Lite(1280×1440 4*15fps),1080N(960×1080 4*25fps),720P(1280×720 4*30fps), 960H(960×480 4*30fps) Pure IP(H.265): PAL: 5MP@8×25fps,4MP@9×25fps,3MP@9×25fps,1080P@9×25fps,960P@9×25fps,720P@9×25fps,D1@9×25fps NTSC: 5MP@8×30fps,4MP@9×30fps,3MP@9×30fps,1080P@9×30fps, 960P@9×30fps, 720P@9×30fps, D1@9×30fps
Record Mode	Manual\Timer\Motion Detection\Intelligent
Playback & Backup	
Decode Capability	2*1080P@30fps
Sync Playback	Pure Analog: 3CH 5MP_LITE @12fps,3CH 4MP_LITE @15fps,4CH 1080N@25fps,4CH 720P@30fps Mixture mode: 1CH 5MP@30fps,2CH 5M_LITE@12fps,2CH 1080p@25fps Pure Network: 1CH 5MP @30fps,1CH 4MP @30fps,2CH 1080P@30fps,4CH 720P@30fps
Remote Playback	4 Channel / 1Channel
Search Mode	ALL, Channel, Manual, Time, Date, Motion Detection,Human Detection,Tag
Playback Functions	Play; Pause; Stop; Fast play; Slow Play;Rewind; Next File; Previous File; Next Camera; Previous Camera; Full Screen; Backup Selection; Digital Zoom
Smart Phone Playback	4 Channel
Backup Mode	USB Device(with format FAT 32)/Network/FTP
Network	
Interface	1 RJ-45 10M/100M self-adaptive Ethernet Interface
Network Functions	TCP/IP,HTTP,HTTPS,SMTP,DHCP,FTP,DDNS,RTP,RTSP,RTCP,NTP,UPnP
DDNS	Dyndns, changeip, no-ip, Oray, A-PRESS, MYQSEE, SKDDNS, SMART-EYES, ZEBEYE,HDPROVN,DYNAMIC_PLANET,EASY_PLANET
Web Browser	Edge,IE8-11, Google Chrome , Firefox ,Safari
CMS Software	Support Windows 7/ Windows 8/Windows 10/Windows 11/MAC OS
Extra Stream	CIF/D1(1-30fps)
Smart Phone	iPhone, Android
Hard Disk Driver	
Interface Type	1 SATA Interface
Capacity	1 SATA Hard Disk (2.5"/3.5" SATA, Up to 8TB)
General	
Language	Simplified Chinese,Traditional Chinese, English, Polish, Czech, Russian, Thai, Hebrew, Arabic, Bulgarian, Japanese,German, French, Portuguese, Turkic, Spanish, Italian, Hungarian, Romanian, korean, Dutch, Greek, Vietnamese, Ukrainian
UTC Control	YES
USB Interface	2 USB 2.0 Interfaces
Power consumption	DC 12V/1.5A ≤ 7W (without HDD)
Working Environment	-10~55 °C/10~90%
Dimension (W×D×H)	260* 230*43(mm)
Weight	0.86Kg (Without HDD)