



## SPECIFICATION

<b>Model NO.</b>	<b>XVRT3004C4PB200</b>
<b>Package</b>	
XVR	1x XVR3004C1N
Camera	4 xBPSCHTC200F-ECO
Cable	4x 18m BNC+DC Cable, 1 x 4CH Power Splitter Cable
Mouse	1xUSB 2.0 Mouse
Hard Disk	No
Adaptor	2 x DC12V2A Adaptor
Weight	
<b>Camera Model</b>	
<b>BPSCHTC200F-ECO</b>	
Image Sensor	1/3" CMOS Sensor
Image Resolution	2M:1920*1080
TV System	PAL/NTSC
Electronic Shutter	AUTO
Minimum Illumination	Color : 0.01 lux@F2.0, AGC ON; B/W : 0 lux with IR
Scanning System	Progressive Scan
<b>Lens</b>	
Focus Length	3.6mm
Focus Control	Fixed
Lens Type	Fixed
<b>Night Vision</b>	
IR Cut Filter	YES
Infrared LED	42μ x 2PCS
Infrared Distance	25M
IR Status	AGC auto control
<b>Camera Features</b>	
Starlight	Color/ B&W (IR-CUT )
Day/Night	YES
OSD Menu	YES
WDR	DWDR
UTC	YES
Noise Reduction	3D NR
Coaxial Audio	NO
White Balance	AUTO / MANUAL
Gain Control	AUTO

## General

Housing	Plastic, IP66
Bracket	YES
Operation Temperature	-10℃ ~ +60℃ RH95% Max
Storage Temperature	-20℃ ~ +60℃ RH95% Max
Power Source	DC12V±10%, 550mA
Dimension	174(W) x 68(H) x 70(D)mm
Weight	295g
<b>Model</b>	<b>XVR3004C1N</b>

## System

Main Processor	MC6630
Operating System	Embedded LINUX

## Video

Input	Analog: 4*(TVI/AHD: 5M@12fps; AHD/TVI/CVI: 4M@15fps; AHD/TVI/CVI: 1080P/720P@30fps; Analog: 960H) Analog+Network: 2*Analog(5MP)+4*network(MAX 5MP) Network: 9*5MP/4MP/3MP/1080P/960P/720P(Total incoming bandwidth ≤48M)
Input	4CH BNC
Signal Type	Analog/AHD/CVI/TVI 2.0/TVI 3.0/Network
Output	1HD,1 VGA

## Audio

Input	1 ChannelRCA,support AOC
Two-way Audio	NO
Output	1 Channel RCA

## Alarm

Sensor Input	NO
Output	NO
Motion Detection	4 Channel(max 9 Channel in pure network mode)
Trigger Events	Recording, Email, Screen tips, Push notifications(motion detection)
Email Alarm	Send Image to The Designated E-mail

## AI Function

Human Detection	YES
-----------------	-----

## PTZ

Interface	NO
Protocol	Coaxial Control
Baud Rate	NO
Address	NO

## Display

VGA	Resolution:1920 × 1080P, 1280 × 1024 , 1280 × 720,1024 × 768
HD Output	Resolution:1920 × 1080P, 1280 × 1024 , 1280 × 720,1024 × 768
Display Split	1/4/8/9
Privacy Masking	3 Rectangular Zones (Each camera)
OSD	Camera title, Time, Video loss, Motion detection, Recording

## Recording

Video Compression	H.265/H.264
Audio Compression	G.711U/G.711A
Resolution	5MP_Lite(1280×1952),4MP_Lite(1280×1440),1080N(960×1080),720P(1280×720),960H(960×480)
Video Quality	Lowest/Low/Ordinary/Good/Better/Best

Record Rate	Analog: PAL: 5MP_Lite(1296×1944 4*12fps),4MP_Lite(1280×1440 4*15fps),1080N(960×1080 4*25fps),720P(1280×720 4*25fps), 960H(960×480 4*25fps) NTSC:5MP_Lite(1296×1944 4*12fps),4MP_Lite(1280×1440 4*15fps),1080N(960×1080 4*25fps),720P(1280×720 4*30fps), 960H(960×480 4*30fps) Pure IP(H.265): PAL: 5MP@8×25fps,4MP@9×25fps,3MP@9×25fps,1080P@9×25fps,960P@9×25fps,720P@9×25fps,D1@9×25fps NTSC: 5MP@8×30fps,4MP@9×30fps,3MP@9×30fps,1080P@9×30fps, 960P@9×30fps, 720P@9×30fps, D1@9×30fps
Record Mode	Manual\Timer\Motion Detection\Intelligent
<b>Playback &amp; Backup</b>	
Decode Capability	2*1080P@30fps
Sync Playback	Pure Analog: 3CH 5MP_LITE @12fps,3CH 4MP_LITE @15fps,4CH 1080N@25fps,4CH 720P@30fps Mixture mode: 1CH 5MP@30fps,2CH 5M_LITE@12fps,2CH 1080p@25fps Pure Network: 1CH 5MP @30fps,1CH 4MP @30fps,2CH 1080P@30fps,4CH 720P@30fps
Remote Playback	4 Channel / 1Channel
Search Mode	ALL, Channel, Manual, Time, Date, Motion Detection,Human Detection,Tag
Playback Functions	Play; Pause; Stop; Fast play; Slow Play;Rewind; Next File; Previous File; Next Camera; Previous Camera; Full Screen; Backup Selection; Digital Zoom
Smart Phone Playback	4 Channel
Backup Mode	USB Device(with format FAT 32 )/Network/FTP
<b>Network</b>	
Interface	1 RJ-45 10M/100M self-adaptive Ethernet Interface
Network Functions	TCP/IP,HTTP,HTTPS,SMTP,DHCP,FTP,DDNS,RTP,RTSP,RTCP,NTP,UPnP
DDNS	Dyndns, changeip, no-ip, Oray, A-PRESS, MYQSEE, SKDDNS, SMART-EYES, ZEBEYE,HDPROVN,DYNAMIC_PLANET,EASY_PLANET
Web Browser	Edge,IE8-11, Google Chrome , Firefox ,Safari
CMS Software	Support Windows 7/ Windows 8/Windows 10/Windows 11/MAC OS
Extra Stream	CIF/D1(1-30fps)
Smart Phone	iPhone, Android
<b>Hard Disk Driver</b>	
Interface Type	1 SATA Interface
Capacity	1 SATA Hard Disk (2.5"/3.5" SATA, Up to 8TB)
<b>General</b>	
Language	Simplified Chinese,Traditional Chinese, English, Polish, Czech, Russian, Thai, Hebrew, Arabic, Bulgarian, Japanese,German, French, Portuguese, Turkic, Spanish, Italian, Hungarian, Romanian, korean, Dutch, Greek, Vietnamese, Ukrainian
UTC Control	YES
USB Interface	2 USB 2.0 Interfaces
Power consumption	DC 12V/1.5A ≤ 7W (without HDD)
Working Environment	-10~55℃ /10~90%
Dimension (W×D×H)	260* 230*43(mm)
Weight	0.86Kg (Without HDD)