



SPECIFICATION

Model NO.	XVRT3004D4PD200
Package	
XVR	1x XVRT3004D
Camera	4 x LIRDLAAD200F
Cable	4x 18m BNC+DC Cable, 1 x 4CH Power Splitter Cable
Mouse	1xUSB 2.0 Mouse
Hard Disk	No
Adaptor	2 x DC12V2A Adaptor
Weight	7.9kg/SET
Camera Model	
LIRDLAAD200F	
Image Sensor	1/2.9" CMOS Sensor
Image Resolution	2M:1920*1080
TV System	PAL/NTSC
Electronic Shutter	AUTO
Minimum Illumination	Color : 0.01 lux@F2.0, AGC ON; B/W : 0 lux with IR
Scanning System	Progressive Scan
Lens	
Focus Length	3.6mm
Focus Control	Fixed
Lens Type	Fixed
Night Vision	
IR Cut Filter	YES
Infrared LED	14μ x 18PCS
Infrared Distance	20M
IR Status	AGC Auto Control
Camera Features	
Starlight	N/A
Day/Night	YES
OSD Menu	YES
WDR	DWDR
UTC	YES
Noise Reduction	3D NR
White Balance	AUTO / MANUAL
Gain Control	AUTO
General	

Housing	Plastic
Bracket	NO
Operation Temperature	-10℃ ~ +60℃ RH95% Max
Storage Temperature	-20℃ ~ +60℃ RH95% Max
Power Source	DC12V±10%, 550mA
Dimension	99(W) x 81(H) x 80(D)mm
Weight	300g
Model	XVRT3004D
System	
Main Processor	MC6630
Operating System	Embedded LINUX
Video	
Input	Normal Mode: Analog: 4*(TVI/AHD: 5M@12fps; AHD/TVI/CVI: 4M@15fps; AHD/TVI: 3M@18fps; AHD/TVI/CVI: 1080P/720P; Analog: 960H) Analog+Network: 2*Analog(5MP@12fps;4MP@15fps;@3MP@18fps;2MP)+4*network(MAX 2MP) Network: 9*5MP/4MP/3MP/1080P/960P/720P(Total incoming bandwidth ≤48M)
Input	4CH BNC
Signal Type	Analog/AHD/CVI/TVI 2.0/TVI 3.0/Network
Output	1HD,1 VGA
Audio	
Input	1 Channel, RCA
Two-way Audio	NO
Output	1 Channel, RCA
Alarm	
Sensor Input	NO
Output	NO
Motion Detection	4 Channel(max 9 Channel in pure network mode)
Trigger Events	Recording, Email, Screen tips, Buzzer, Push notifications(motion detection)
Email Alarm	Send Image to The Designated E-mail
AI Function	
Human Detection	YES
PTZ	
Interface	RS485
Protocol	Pelco-D, Pelco-P
Baud Rate	110~921600
Address	0~255
Display	
VGA	Resolution: 1920 × 1080P/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz,1024 × 768/60Hz
HD Output	Resolution:1920 × 1080P/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz,1024 × 768/60Hz
Display Split	9 Channel/4 Channel / 1Channel
Privacy Masking	3 Rectangular Zones (Each camera)
OSD	Camera title, Time, Video loss, Alarm, Motion detection, Recording
Recording	
Video Compression	H.265/H.264
Audio Compression	G.711u/G.711a
Resolution	5MP_Lite(1296×1944),4MP_Lite(1280×1440),3MP_Lite(1024×1536),1080N(960×1080),720P(1280×720),960H(P:960×576/N:960×480)
Video Quality	Lowest/Low/Ordinary/Good/Better/Best
Record Rate	Analog: PAL:5MP_Lite(1296×1944 4*8fps),4MP_Lite(1280×1440 4*15fps),3MP_Lite(1024×1536 4*18fps),1080N(960×1080 4*18fps),720P(1280×720 4*20fps), 960H(960×480 4*25fps) NTSC: 5MP_Lite(1296×1944 4*8fps),4MP_Lite(1280×1440 4*15fps),3MP_Lite(1024×1536 4*18fps),1080N(960×1080 4*18fps),720P(1280×720 4*20fps), 960H(960×480 4*25fps) Pure IP(H.265): PAL: 5MP@8×25fps,4MP@9×25fps,3MP@9×25fps,1080P@9×25fps,960P@9×25fps,720P@9×25fps,D1@9×25fps NTSC: 5MP@8×30fps,4MP@9×30fps,3MP@9×30fps,1080P@9×30fps, 960P@9×30fps, 720P@9×30fps, D1@9×30fps

Record Mode	Manual\Timer\Motion Detection
Playback & Backup	
Decode Capability	2CH 1080P@30fps
Sync Playback	Pure Analog: 4CH 960H@25fps, 2CH 720P@20fps, 2CH 1080N@18fps, 1CH 5M_LITE@8fps, 1CH 4M_LITE@15fps, 1CH 3M_LITE@18fps Mixture mode: 4CH 720P@25fps, 2CH 1080P@25fps, 1CH 5M_LITE@8fps, 1CH 4M_LITE@15fps, 1CH 3M_LITE@18fps Pure Network: 4CH*720P@25fps, 2CH 1080P@25fps, 1CH 5MP@25fps
Remote Playback	1Channel
Search Mode	ALL, Channel, Manual, Time, Date, Motion Detection
Playback Functions	Play, Pause, Stop, Fast play, Slow play, Rewind, Single frame forward/back, Digital Zoom, Full screen
Smart Phone Playback	4 Channel
Backup Mode	USB Device(with format FAT 32)/Network/FTP
Network	
Interface	1 RJ45 10M/100M Adaptive Ethernet Interface
Network Functions	TCP/IP, HTTP, UPnP, DNS, NTP, SMTP,DHCP, FTP, DDNS, RTP, RTSP, RTCP
DDNS	Dyndns, changeip, no-ip, Oray, A-PRESS, MYQSEE, SKDDNS, SMART-EYES, ZEBEYE,HDPROVN
Web Browser	Edge,IE8-11, Google Chrome , Firefox ,Safari
CMS Software	Support Windows 7/ Windows 8/Windows 10
Extra Stream	CIF/D1(1~25fps)
Smart Phone	iPhone, iPad, Android ,Android pad
Hard Disk Driver	
Interface Type	1 SATA Interface
Capacity	1 SATA Hard Disk (2.5"/3.5" SATA, Up to 8TB)
General	
Language	Simplified Chinese,Traditional Chinese, English, Polish, Czech, Russian, Thai, Hebrew, Arabic, Bulgarian, Japanese, German, French, Portuguese, Turkic, Spanish, Italian, Hungarian, Romanian, Korean, Dutch, Greek, Vietnamese,
UTC Control	YES
USB Interface	2 USB 2.0 Interfaces
Power consumption	DC 12V/2A ≤10W (Without Hard Disk)
Working Environment	-10~55°C/10~90%
Dimension (W×D×H)	260*215*43(mm)
Weight	2kg (Without HDD)